


**SAE 070119**

Ref. Aeroquip 202712  
 Ref. Parker LHTX / 03L3  
 Ref. Weatherhead C5306

**2403LH**  
**Large Hex Union**



2403LH-①-② ① -MJ ② -MJ	Tube O.D.	① Male JIC	② Male JIC	C Hex	D Drill	L Length	Operating Pressure
2403LH-04-04	1/4	7/16 - 20	7/16 - 20	11/16	0.172	1.37	7,500
2403LH-05-05	5/16	1/2 - 20	1/2 - 20	3/4	0.234	1.37	6,000
2403LH-06-06	3/8	9/16 - 18	9/16 - 18	13/16	0.297	1.41	6,000
2403LH-08-06	1/2 x 3/8	3/4 - 16	9/16 - 18	1"	0.297	1.52	6,000
2403LH-08-08	1/2	3/4 - 16	3/4 - 16	1"	0.391	1.62	6,000
2403LH-10-10	5/8	7/8 - 14	7/8 - 14	1 1/8	0.484	1.88	5,000
2403LH-12-12	3/4	1 1/16 - 12	1 1/16 - 12	1 3/8	0.609	2.16	5,000
2403LH-16-16	1"	1 5/16 - 12	1 5/16 - 12	1 5/8	0.844	2.25	4,000
2403LH-20-20	1 1/4	1 5/8 - 12	1 5/8 - 12	1 7/8	1.078	2.43	4,000
2403LH-24-24	1 1/2	1 7/8 - 12	1 7/8 - 12	2 1/8	1.312	2.75	3,000

4:1 Safety Factor

37° JIC  
Flare

37° JIC Flare fittings seal on the flare. Careful handling will prevent damage and leaks.

**i** Informational Tips

**Over-Torque Abuse** can lead to fitting damage resulting in leakage. Use proper torque specifications regarding thread type and size.

**i** Informational Tips

Ask for our **Brass Fittings and Barbs** catalog.