


37° JIC Flare

PRESSURE CONNECTIONS CORP.

2404L / LL Male Connector Long & Double Long



SAE 070102 ①

Ref. Aeroquip 202113 / 202114
Ref. Parker FFTX


37° JIC
Flare

2404L-①-② ①-MJ ②-MP	Tube O.D.	① Male JIC	② Male NPTF	C Hex	D Drill	D1 Drill	L Length	Operating Pressure
2404L-04-02	1/4	7/16 - 20	1/8 - 27	1/2	0.172	0.172	1.81	6,000
2404L-04-04	1/4	7/16 - 20	1/4 - 18	5/8	0.172	0.281	2.25	6,000
2404L-05-04	5/16	1/2 - 20	1/4 - 18	9/16	0.234	0.234	2.25	6,000
2404L-06-04	3/8	9/16 - 18	1/4 - 18	5/8	0.297	0.281	2.25	6,000
2404L-06-06	3/8	9/16 - 18	3/8 - 18	3/4	0.297	0.297	2.50	6,000
2404L-08-06	1/2	3/4 - 16	3/8 - 18	13/16	0.391	0.406	2.75	6,000
2404L-12-12	3/4	1 1/16 - 12	3/4 - 14	1 1/8	0.609	0.609	3.50	5,000
2404L-16-16	1"	1 5/16 - 12	1 - 11 1/2	1 3/8	0.844	0.844	4.00	3,000
2404LL - Male Connector Double Long								
2404LL-04-02	1/4	7/16 - 20	1/8 - 27	1/2	0.172	0.188	2.56	5,000

① Length is not specified in SAE.

4:1 Safety Factor

2404R Restrictor Male Connector



SAE 070102

2404R-①-②-③ ①-MJ ②-MP ③-Orifice	Tube O.D.	① Male JIC	② Male NPTF	③ Orifice	C Hex	D Drill	L Length	Operating Pressure
2404R-06-06-.031	3/8	9/16 - 18	3/8 - 18	1/32	3/4	0.297	1.43	6,000
2404R-06-06-.062	3/8	9/16 - 18	3/8 - 18	1/16	3/4	0.297	1.43	6,000
2404R-06-08-.031	3/8	9/16 - 18	1/2 - 14	1/32	7/8	0.297	1.69	6,000
2404R-06-08-.062	3/8	9/16 - 18	1/2 - 14	1/16	7/8	0.297	1.69	6,000

4:1 Safety Factor

③ We can also drill the blank restrictor (.000) to your specifications.

③ More RESTRICTOR fittings

1404R (pg. 43)	6400R (pg. 134)
1501R (pg. 47)	6801R (pg. 157)
2404R (pg. 70)	6900R (pg. 167)
2406R (pg. 73)	6901R (pg. 169)
5405R (pg. 114)	6902R (pg. 171)