


**SAE 070103**

Ref. Aeroquip 2022  
 Ref. Parker GTX / O203  
 Ref. Weatherhead C5255



**2405**  
**Female Connector**  
**Male JIC x Female Pipe**

2405-①-② ① -MJ ② -FP	Tube O.D.	① Male JIC	② Female NPTF	C Hex	D Drill	L Length	Operating Pressure
2405-02-02	1/8	5/16 - 24	1/8 - 27	9/16	0.062	1.12	6,000
2405-03-02	3/16	3/8 - 24	1/8 - 27	9/16	0.125	1.13	6,000
2405-04-02	1/4	7/16 - 20	1/8 - 27	9/16	0.172	1.19	6,000
2405-04-04	1/4	7/16 - 20	1/4 - 18	3/4	0.172	1.42	6,000
2405-04-06	1/4	7/16 - 20	3/8 - 18	7/8	0.172	1.45	6,000
2405-05-02	5/16	1/2 - 20	1/8 - 27	9/16	0.234	1.17	6,000
2405-05-04	5/16	1/2 - 20	1/4 - 18	3/4	0.234	1.40	6,000
2405-06-02	3/8	9/16 - 18	1/8 - 27	5/8	0.297	1.19	6,000
2405-06-04	3/8	9/16 - 18	1/4 - 18	3/4	0.297	1.40	6,000
2405-06-06	3/8	9/16 - 18	3/8 - 18	7/8	0.297	1.46	6,000
2405-06-08	3/8	9/16 - 18	1/2 - 14	1 1/8	0.297	1.70	5,000
2405-08-04	1/2	3/4 - 16	1/4 - 18	13/16	0.391	1.55	6,000
2405-08-06	1/2	3/4 - 16	3/8 - 18	7/8	0.391	1.56	6,000
2405-08-08	1/2	3/4 - 16	1/2 - 14	1 1/8	0.391	1.80	5,000
2405-08-12	1/2	3/4 - 16	3/4 - 14	1 3/8	0.391	1.86	4,000
2405-10-06	5/8	7/8 - 14	3/8 - 18	15/16	0.484	1.67	5,000
2405-10-08	5/8	7/8 - 14	1/2 - 14	1 1/8	0.484	1.89	5,000
2405-10-12	5/8	7/8 - 14	3/4 - 14	1 3/8	0.484	1.95	4,000
2405-12-08	3/4	1 1/16 - 12	1/2 - 14	1 1/8	0.609	2.05	5,000
2405-12-12	3/4	1 1/16 - 12	3/4 - 14	1 3/8	0.609	2.06	4,000
2405-12-16	3/4	1 1/16 - 12	1 - 11 1/2	1 3/8	0.484	1.95	3,000
2405-14-12	7/8	1 3/16 - 12	3/4 - 14	1 3/8	0.719	2.06	4,000
2405-16-12	1"	1 5/16 - 12	3/4 - 14	1 5/8	0.844	2.35	4,000
2405-16-16	1"	1 5/16 - 12	1 - 11 1/2	1 5/8	0.844	2.35	3,000
2405-16-20	1"	1 5/16 - 12	1 1/4 - 11 1/2	2"	0.844	2.43	2,500
2405-20-16	1 1/4	1 5/8 - 12	1 - 11 1/2	2"	1.078	2.49	3,000
2405-20-20	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	2"	1.078	2.49	2,500
2405-20-24	1 1/4	1 5/8 - 12	1 1/2 - 11 1/2	2 3/8	1.078	2.51	2,000
2405-24-20	1 1/2	1 7/8 - 12	1 1/4 - 11 1/2	2 3/8	1.312	2.59	2,500
2405-24-24	1 1/2	1 7/8 - 12	1 1/2 - 11 1/2	2 3/8	1.312	2.62	2,000
2405-32-24	2"	2 1/2 - 12	1 1/2 - 11 1/2	2 7/8	1.781	2.95	2,000
2405-32-32	2"	2 1/2 - 12	2 - 11 1/2	2 7/8	1.781	2.97	1,500

37° JIC  
Flare

4:1 Safety Factor