


37° JIC Flare

PRESSURE CONNECTIONS CORP.

2407 Insert Tube Reducer



SAE 070123

Ref. Aeroquip 2215 / 221501
Ref. Parker TRTX / TRTXN

Used w/ Tube Nut (318) on page 37

37° JIC
Flare

2407-①-② ①-FJ ②-MJ	Tube O.D.	① Female JIC	② Male JIC	D Drill	L Length	Operating Pressure
2407-06-04	3/8	9/16 - 18	7/16 - 20	0.172	0.97	6,000
2407-08-04	1/2	3/4 - 16	7/16 - 20	0.172	1.00	6,000
2407-08-06	1/2	3/4 - 16	9/16 - 18	0.297	1.00	6,000
2407-10-04	5/8	7/8 - 14	7/16 - 20	0.172	1.03	5,000
2407-10-06	5/8	7/8 - 14	9/16 - 18	0.297	1.03	5,000
2407-12-04	3/4	1 1/16 - 12	7/16 - 20	0.172	1.09	5,000
2407-12-06	3/4	1 1/16 - 12	9/16 - 18	0.297	1.09	5,000
2407-12-08	3/4	1 1/16 - 12	3/4 - 16	0.391	1.18	5,000
2407-16-04	1"	1 5/16 - 12	7/16 - 20	0.172	1.16	4,000
2407-16-06	1"	1 5/16 - 12	9/16 - 18	0.297	1.16	4,000
2407-16-08	1"	1 5/16 - 12	3/4 - 16	0.391	1.26	4,000
2407-16-10	1"	1 5/16 - 12	7/8 - 14	0.484	1.36	4,000
2407-16-12	1"	1 5/16 - 12	1 1/16 - 12	0.609	1.47	4,000
2407-20-08	1 1/4	1 5/8 - 12	3/4 - 16	0.391	1.34	4,000
2407-20-12	1 1/4	1 5/8 - 12	1 1/16 - 12	0.609	1.55	4,000
2407-20-16	1 1/4	1 5/8 - 12	1 5/16 - 12	0.844	1.59	4,000
2407-24-08	1 1/2	1 7/8 - 12	3/4 - 16	0.391	1.41	3,000
2407-24-10	1 1/2	1 7/8 - 12	7/8 - 14	0.484	1.51	3,000

4:1 Safety Factor

37° JIC Flare information is on page 64.

QA Quality Assurance Tips

We maintain our prints and update our manufacturing processes to the Latest SAE Standards.