


37° JIC Flare

PRESSURE CONNECTIONS CORP.

2501LL Male Elbow Double Long



SAE 071602


Ref. Aeroquip 202413
Ref. Parker CCCTX / 5703
Ref. Weatherhead C5435

37° JIC
Flare

2501LL-①-② ①-MJ ②-MP	Tube O.D.	① Male JIC	② Male NPTF	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
2501LL-04-02-4	1/4	7/16 - 20	1/8 - 27	0.172	0.188	0.89	1.56	7/16	6,000
2501LL-04-04-4	1/4	7/16 - 20	1/4 - 18	0.172	0.281	1.05	2.03	9/16	6,000
2501LL-05-02-4	5/16	1/2 - 20	1/8 - 27	0.234	0.188	0.95	1.63	9/16	6,000
2501LL-05-04-4	5/16	1/2 - 20	1/4 - 18	0.234	0.281	1.05	2.04	9/16	6,000
2501LL-06-04-4	3/8	9/16 - 18	1/4 - 18	0.297	0.281	1.06	2.07	9/16	6,000
2501LL-06-06-4	3/8	9/16 - 18	3/8 - 18	0.297	0.406	1.14	2.42	3/4	6,000
2501LL-06-08-4	3/8	9/16 - 18	1/2 - 14	0.297	0.531	1.22	2.84	7/8	6,000
2501LL-08-06-4	1/2	3/4 - 16	3/8 - 18	0.391	0.406	1.25	2.42	3/4	6,000
2501LL-08-08-4	1/2	3/4 - 16	1/2 - 14	0.391	0.531	1.33	2.84	7/8	6,000
2501LL-10-08-4	5/8	7/8 - 14	1/2 - 14	0.484	0.531	1.45	2.87	7/8	5,000
2501LL-12-12-4	3/4	1 1/16 - 12	3/4 - 14	0.609	0.719	1.66	3.28	1 1/16	4,000
2501LL-14-12	7/8	1 3/16 - 12	3/4 - 14	0.719	0.719	1.80	3.63	1 1/4	4,000
2501LL-16-12	1"	1 5/16 - 12	3/4 - 14	0.844	0.719	1.81	3.41	1 3/8	4,000
2501LL-16-16-4	1"	1 5/16 - 12	1 - 11 1/2	0.844	0.938	1.81	4.05	1 5/16	3,000
2501LL-20-20	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	1.078	1.250	2.06	4.94	1 3/4	2,500

4:1 Safety Factor

2501LLL Male Elbow Triple Long



SAE 071602 ①

Ref. Aeroquip 202414

2501LLL-①-② ①-MJ ②-MP	Tube O.D.	① Male JIC	② Male NPTF	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
2501LLL-04-02	1/4	7/16 - 20	1/8 - 27	0.172	0.188	0.89	2.31	1/2	6,000
2501LLL-04-04	1/4	7/16 - 20	1/4 - 18	0.172	0.281	0.95	3.06	5/8	6,000
2501LLL-06-04	3/8	9/16 - 18	1/4 - 18	0.297	0.281	1.06	3.06	5/8	6,000
2501LLL-06-06	3/8	9/16 - 18	3/8 - 18	0.297	0.406	1.14	3.57	13/16	6,000
2501LLL-08-06	1/2	3/4 - 16	3/8 - 18	0.391	0.406	1.25	3.75	13/16	6,000
2501LLL-10-08	5/8	7/8 - 14	1/2 - 14	0.484	0.531	1.45	4.50	15/16	5,000
2501LLL-12-12	3/4	1 1/16 - 12	3/4 - 14	0.609	0.719	1.66	5.03	1 1/8	4,000

① Triple length is not specified in SAE.

4:1 Safety Factor