


37° JIC Flare

PRESSURE CONNECTIONS CORP.

2601 Male Branch Tee



SAE 070425

Ref. Aeroquip 2030
Ref. Parker STX / 213T
Ref. Weatherhead C5605

37° JIC
Flare

2601-①-②-③ ①-MJ ②-MJ ③-MP	Tube O.D.	①② Male JIC	③ Male NPTF	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
2601-03-03-02-4	3/16	3/8 - 24	1/8 - 27	0.125	0.188	0.83	0.72	7/16	6,000
2601-04-04-02-4	1/4	7/16 - 20	1/8 - 27	0.172	0.188	0.89	0.78	7/16	6,000
2601-04-04-04-4	1/4	7/16 - 20	1/4 - 18	0.172	0.281	1.05	1.09	9/16	6,000
2601-04-04-06-4	1/4	7/16 - 20	3/8 - 18	0.172	0.406	1.12	1.22	3/4	6,000
2601-05-05-02-4	5/16	1/2 - 20	1/8 - 27	0.234	0.188	0.95	0.78	9/16	6,000
2601-05-05-04-4	5/16	1/2 - 20	1/4 - 18	0.234	0.281	1.05	1.09	9/16	6,000
2601-06-06-02	3/8	9/16 - 18	1/8 - 27	0.297	0.188	1.06	0.90	9/16	6,000
2601-06-06-04	3/8	9/16 - 18	1/4 - 18	0.297	0.281	1.06	1.09	5/8	6,000
2601-06-06-04-4	3/8	9/16 - 18	1/4 - 18	0.297	0.281	1.06	1.09	9/16	6,000
2601-06-06-06	3/8	9/16 - 18	3/8 - 18	0.297	0.406	1.14	1.22	3/4	6,000
2601-06-06-06-4	3/8	9/16 - 18	3/8 - 18	0.297	0.406	1.14	1.22	3/4	6,000
2601-06-06-08-4	3/8	9/16 - 18	1/2 - 14	0.297	0.531	1.22	1.47	7/8	6,000
2601-08-08-04	1/2	3/4 - 16	1/4 - 18	0.391	0.280	1.25	1.19	13/16	6,000
2601-08-08-06-4	1/2	3/4 - 16	3/8 - 18	0.391	0.406	1.25	1.22	3/4	6,000
2601-08-08-08-4	1/2	3/4 - 16	1/2 - 14	0.391	0.531	1.33	1.47	7/8	6,000
2601-10-10-06	5/8	7/8 - 14	3/8 - 18	0.484	0.406	1.45	1.28	15/16	5,000
2601-10-10-08-4	5/8	7/8 - 14	1/2 - 14	0.484	0.531	1.45	1.47	7/8	5,000
2601-10-10-12	5/8	7/8 - 14	3/4 - 14	0.484	0.688	1.54	1.59	1 1/8	4,000
2601-12-12-08-4	3/4	1 1/16 - 12	1/2 - 14	0.609	0.531	1.66	1.59	1 1/16	5,000
2601-12-12-12-4	3/4	1 1/16 - 12	3/4 - 14	0.609	0.719	1.66	1.59	1 1/16	4,000
2601-14-14-12-4	7/8	1 3/16 - 12	3/4 - 14	0.719	0.719	1.81	1.72	1 5/16	4,000
2601-16-16-12	1"	1 5/16 - 12	3/4 - 14	0.844	0.719	1.81	1.72	1 3/8	4,000
2601-16-16-16-4	1"	1 5/16 - 12	1 - 11 1/2	0.844	0.938	1.81	1.97	1 5/16	3,000
2601-20-20-20-4	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	1.078	1.250	2.06	2.38	1 5/8	2,500
2601-32-32-32-4	2"	2 1/2 - 12	2 - 11 1/2	1.781	1.938	3.06	3.00	2 1/2	2,000

4:1 Safety Factor

37° JIC Flare information is on page 64.