


SAE 070424

Ref. Aeroquip 2028
 Ref. Parker RTX / D13T
 Ref. Weatherhead C5755



2605
Male Run Tee

2605-①-②-③ ① -MJ ② -MP ③ -MJ	Tube O.D.	①③ Male JIC	② Male NPTF	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
2605-03-02-03-4	3/16	3/8 - 24	1/8 - 27	0.125	0.188	0.83	0.72	7/16	6,000
2605-04-02-04-4	1/4	7/16 - 20	1/8 - 27	0.172	0.188	0.89	0.78	7/16	6,000
2605-04-04-04-4	1/4	7/16 - 20	1/4 - 18	0.172	0.281	1.05	1.09	9/16	6,000
2605-05-02-05-4	5/16	1/2 - 20	1/8 - 27	0.234	0.188	0.97	0.81	9/16	6,000
2605-05-04-05	5/16	1/2 - 20	1/4 - 18	0.234	0.281	0.97	1.09	9/16	6,000
2605-06-04-06-4	3/8	9/16 - 18	1/4 - 18	0.297	0.281	1.06	1.09	9/16	6,000
2605-06-06-06-4	3/8	9/16 - 18	3/8 - 18	0.297	0.406	1.14	1.22	3/4	6,000
2605-08-04-08	1/2	3/4 - 16	1/4 - 18	0.390	0.281	1.25	1.19	13/16	6,000
2605-08-06-08-4	1/2	3/4 - 16	3/8 - 18	0.391	0.406	1.25	1.22	3/4	6,000
2605-08-08-08-4	1/2	3/4 - 16	1/2 - 14	0.391	0.531	1.33	1.47	7/8	6,000
2605-10-08-10-4	5/8	7/8 - 14	1/2 - 14	0.484	0.531	1.45	1.47	7/8	5,000
2605-10-12-10	5/8	7/8 - 14	3/4 - 14	0.484	0.719	1.55	1.59	1 1/8	4,000
2605-12-08-12	3/4	1 1/16 - 12	1/2 - 14	0.609	0.531	1.66	1.56	1 1/8	5,000
2605-12-12-12-4	3/4	1 1/16 - 12	3/4 - 14	0.609	0.719	1.66	1.59	1 1/16	4,000
2605-14-12-14-4	7/8	1 3/16 - 12	3/4 - 14	0.719	0.719	1.80	1.69	1 5/16	4,000
2605-16-16-16-4	1"	1 5/16 - 12	1 - 11 1/2	0.844	0.938	1.81	1.97	1 5/16	3,000
2605-20-20-20-4	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	1.078	1.250	2.06	2.38	1 5/8	2,500
2605-24-24-24-4	1 1/2	1 7/8 - 12	1 1/2 - 11 1/2	1.312	1.500	2.33	2.64	1 7/8	2,500
2605-32-32-32-4	2"	2 1/2 - 12	2 - 11 1/2	1.781	1.938	3.06	3.00	2 1/2	2,000

37° JIC
Flare

4:1 Safety Factor



We maintain our prints and update our manufacturing processes to the Latest SAE Standards.