


37° JIC Flare

PRESSURE CONNECTIONS CORP.

2606 Female Run Tee



SAE 070426

Ref. Aeroquip 2029
Ref. Parker MTX / 023T
Ref. Weatherhead C5805

37° JIC
Flare

2606-①-②-③ ①-MJ ②-FP ③-MJ	Tube O.D.	①③ Male JIC	② Female NPTF	D Drill	M Length	N Length	Y Flats	Operating Pressure
2606-04-02-04-4	1/4	7/16 - 20	1/8 - 27	0.172	1.08	0.66	9/16	5,000
2606-04-04-04-4	1/4	7/16 - 20	1/4 - 18	0.172	1.22	0.88	3/4	5,000
2606-06-04-06-4	3/8	9/16 - 18	1/4 - 18	0.297	1.23	0.88	3/4	5,000
2606-06-06-06-4	3/8	9/16 - 18	3/8 - 18	0.297	1.24	1.02	7/8	4,500
2606-08-04-08-4	1/2	3/4 - 16	1/4 - 18	0.391	1.42	1.02	7/8	4,500
2606-08-06-08-4	1/2	3/4 - 16	3/8 - 18	0.391	1.42	1.02	7/8	4,500
2606-08-08-08-4	1/2	3/4 - 16	1/2 - 14	0.391	1.52	1.23	1 1/16	3,000
2606-10-08-10-4	5/8	7/8 - 14	1/2 - 14	0.539	1.64	1.23	1 1/16	3,000
2606-12-12-12-4	3/4	1 1/16 - 12	3/4 - 14	0.609	1.89	1.36	1 5/16	3,000
2606-14-12-14-4	7/8	1 3/16 - 12	3/4 - 14	0.719	1.80	1.42	1 5/16	3,000
2606-16-16-16-4	1"	1 5/16 - 12	1 - 11 1/2	0.844	2.17	1.63	1 5/8	1,800
2606-20-20-20-4	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	1.078	2.33	1.70	1 7/8	2,000
2606-24-24-24	1 1/2	1 7/8 - 12	1 1/2 - 11 1/2	1.312	2.89	2.08	2 3/8	1,500
2606-32-32-32	2"	2 1/2 - 12	2 - 11 1/2	1.781	3.30	2.39	2 7/8	1,200

4:1 Safety Factor

Female Branch Tees (2602 pg. 85) and Female Run Tees (2606 pg. 88)
can also be used as a *Gageport*.