


SAE 140230



1501R
Restrictor MP x NPSM Elbow

Female Pipe Swivels (NPSM)

1501R-①-②-③ ①-MP ②-FPX ③-Orifice	① Male NPTF	② Female NPSM Swivel	③ Orifice	C Nut Hex	D Drill	M Length	N Length	Y Flats	Operating Pressure
1501R-04-04.000	1/4 - 18	1/4 - 18	Blank	11/16	0.281	1.25	0.97	9/16	5,000
1501R-04-04.032	1/4 - 18	1/4 - 18	1/32	11/16	0.281	1.25	0.97	9/16	5,000
1501R-04-04.040	1/4 - 18	1/4 - 18	#60	11/16	0.281	1.25	0.97	9/16	5,000
1501R-04-04.062	1/4 - 18	1/4 - 18	1/16	11/16	0.281	1.25	0.97	9/16	5,000
1501R-06-06.000	3/8 - 18	3/8 - 18	Blank	7/8	0.406	1.19	1.13	3/4	4,000
1501R-06-06.032	3/8 - 18	3/8 - 18	1/32	7/8	0.406	1.19	1.13	3/4	4,000
1501R-06-06.062	3/8 - 18	3/8 - 18	1/16	7/8	0.406	1.19	1.13	3/4	4,000
1501R-08-06.000	1/2 - 14	3/8 - 18	Blank	7/8	0.531	1.47	1.25	7/8	3,500
1501R-08-06.032	1/2 - 14	3/8 - 18	1/32	7/8	0.531	1.47	1.25	7/8	3,500
1501R-08-06.062	1/2 - 14	3/8 - 18	1/16	7/8	0.531	1.47	1.25	7/8	3,500
1501R-08-08.000	1/2 - 14	1/2 - 14	Blank	1"	0.531	1.47	1.40	7/8	3,500
1501R-08-08.032	1/2 - 14	1/2 - 14	1/32	1"	0.531	1.47	1.40	7/8	3,500
1501R-08-08.062	1/2 - 14	1/2 - 14	1/16	1"	0.531	1.47	1.40	7/8	3,500
1501R-12-12.000	3/4 - 14	3/4 - 14	Blank	1 1/4	0.719	1.59	1.65	1 1/16	2,200
1501R-12-12.032	3/4 - 14	3/4 - 14	1/32	1 1/4	0.719	1.59	1.65	1 1/16	2,200
1501R-12-12.062	3/4 - 14	3/4 - 14	1/16	1 1/4	0.719	1.59	1.65	1 1/16	2,200

4:1 Safety Factor

③ We can also drill the blank restrictor (.000) to your specifications.

③ More **RESTRICTOR** fittings

1404R (pg. 43)	6400R (pg. 134)
1501R (pg. 47)	6801R (pg. 157)
2404R (pg. 70)	6900R (pg. 167)
2406R (pg. 73)	6901R (pg. 169)
5405R (pg. 114)	6902R (pg. 171)