


O-Ring Face Seal

PRESSURE CONNECTIONS CORP.

FS-2403 OFS Tube Union



SAE 520101

Ref. Aeroquip FF2000T
Ref. Parker HLO
Ref. Weatherhead 4305

FS-2403-①-② ①-OFS ②-OFS	Tube O.D.	① Male OFS	② Male OFS	C Hex	D Drill	D1 Drill	L Length	Operating Pressure
FS-2403-04-04	1/4	9/16 - 18	9/16 - 18	5/8	0.172	0.172	1.08	9,200
FS-2403-06-04	3/8 x 1/4	11/16 - 16	9/16 - 18	3/4	0.264	0.172	1.17	9,200
FS-2403-06-06	3/8	11/16 - 16	11/16 - 16	3/4	0.264	0.264	1.22	9,200
FS-2403-08-06	1/2 x 3/8	13/16 - 16	11/16 - 16	7/8	0.378	0.264	1.33	9,200
FS-2403-08-08	1/2	13/16 - 16	13/16 - 16	7/8	0.378	0.378	1.39	9,200
FS-2403-10-08	5/8 x 1/2	1 - 14	13/16 - 16	1 1/16	0.484	0.378	1.57	6,000
FS-2403-10-10	5/8	1 - 14	1 - 14	1 1/16	0.484	0.484	1.68	6,000
FS-2403-12-10	3/4 x 5/8	1 3/16 - 12	1 - 14	1 1/4	0.609	0.484	1.80	6,000
FS-2403-12-12	3/4	1 3/16 - 12	1 3/16 - 12	1 1/4	0.609	0.609	1.86	6,000
FS-2403-16-12	1" x 3/4	1 7/16 - 12	1 3/16 - 12	1 1/2	0.811	0.609	1.92	6,000
FS-2403-16-16	1"	1 7/16 - 12	1 7/16 - 12	1 1/2	0.811	0.811	1.94	6,000
FS-2403-20-16	1 1/4 x 1"	1 11/16 - 12	1 7/16 - 12	1 3/4	1.024	0.811	2.02	6,000
FS-2403-20-20	1 1/4	1 11/16 - 12	1 11/16 - 12	1 3/4	1.024	1.024	2.02	6,000
FS-2403-24-20	1 1/2 x 1 1/4	2 - 12	1 11/16 - 12	2 1/8	1.260	1.024	2.09	5,000
FS-2403-24-24	1 1/2	2 - 12	2 - 12	2 1/8	1.260	1.260	2.09	5,000

4:1 Safety Factor

O-Ring Face Seal information is on pages 172-173.



Pressure Connections provides up to date **Gauge Certifications** as part of our equipment and **Gauge Calibration Program**. We out-source our gauge calibrations to ensure inspection consistency.