


**SAE J1453**

Ref. Aeroquip FF2093T  
 Ref. Parker VLO  
 Ref. Weatherhead 4355




**FS-2503**  
**OFS Male Elbow**

FS-2503-①-② ①-OFS ②-MP	Tube O.D.	① Male OFS	② Male Pipe	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
FS-2503-04-04-4	1/4	9/16 - 18	1/4 - 18	0.172	0.281	0.61	0.94	9/16	6,000
FS-2503-06-04-4	3/8	11/16 - 16	1/4 - 18	0.264	0.281	0.72	0.94	3/4	6,000
FS-2503-06-06-4	3/8	11/16 - 16	3/8 - 18	0.264	0.406	0.74	0.87	3/4	6,000
FS-2503-08-08-4	1/2	13/16 - 16	1/2 - 14	0.378	0.531	0.86	1.17	7/8	6,000
FS-2503-10-08-4	5/8	1 - 14	1/2 - 14	0.484	0.531	0.92	1.17	1 1/16	6,000
FS-2503-12-12-4	3/4	1 3/16 - 12	3/4 - 14	0.609	0.719	1.02	1.30	1 3/16	4,000
FS-2503-16-16-4	1"	1 7/16 - 12	1 - 11 1/2	0.811	0.938	1.18	1.48	1 7/16	3,000
FS-2503-20-20-4	1 1/4	1 11/16 - 12	1 1/4 - 11 1/2	1.024	1.250	1.72	2.36	1 5/8	2,500

4:1 Safety Factor

**SAE J1453**

Ref. Aeroquip FF2001T  
 Ref. Parker SLO



**FS-2601**  
**OFS Male Run Tee**

FS-2601-①-②-③ ①-OFS ②-OFS ③-MP	Tube O.D.	①② Male OFS	③ Male Pipe	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
FS-2601-06-06-04-4	3/8	11/16 - 16	1/4 - 18	0.265	0.281	0.99	1.10	3/4	6,000
FS-2601-06-06-06-4	3/8	11/16 - 16	3/8 - 18	0.264	0.406	0.98	1.22	3/4	6,000
FS-2601-08-08-06-4	1/2	13/16 - 16	3/8 - 18	0.378	0.406	1.10	1.22	3/4	6,000
FS-2601-08-08-08-4	1/2	13/16 - 16	1/2 - 14	0.378	0.531	1.10	1.47	7/8	6,000
FS-2601-12-12-12-4	3/4	1 3/16 - 12	3/4 - 14	0.609	0.719	1.43	1.55	1 3/16	4,000

4:1 Safety Factor

O-Ring  
 Face Seal