


O-Ring Face Seal

PRESSURE CONNECTIONS CORP.

FS-2603 OFS Union Tee




SAE 520401

Ref. Aeroquip FF1898T
Ref. Parker JLO
Ref. Weatherhead 4705

FS-2603-①-②-③ ①-OFS ②-OFS ③-OFS	Tube O.D.	①②③ Male OFS	D Drill	M Length	Y Flats	Operating Pressure
FS-2603-04-04-04-4	1/4	9/16 - 18	0.172	0.85	9/16	9,200
FS-2603-06-06-06-4	3/8	11/16 - 16	0.264	0.98	3/4	9,200
FS-2603-08-08-08-4	1/2	13/16 - 16	0.378	1.10	3/4	9,200
FS-2603-10-10-10-4	5/8	1 - 14	0.484	1.31	1 1/16	6,000
FS-2603-12-12-12-4	3/4	1 3/16 - 12	0.609	1.47	1 3/16	6,000
FS-2603-16-16-16-4	1"	1 7/16 - 12	0.811	1.64	1 7/16	6,000
FS-2603-20-20-20	1 1/4	1 11/16 - 12	1.024	1.76	1 5/8	5,000
FS-2603-24-24-24	1 1/2	2 - 12	1.260	1.92	2"	4,000

4:1 Safety Factor

FS-2650 OFS Union Cross



SAE 520501

Ref. Parker KLO
Ref. Weatherhead 4955

FS-2650-①-②-③-④ ①②③④-OFS	Tube O.D.	①②③④ Male OFS	D Drill	M Length	Y Flats	Operating Pressure
FS-2650-04-04-04-04-4	1/4	9/16 - 18	0.172	0.85	9/16	9,200
FS-2650-06-06-06-06-4	3/8	11/16 - 16	0.264	0.96	3/4	9,200
FS-2650-08-08-08-08-4	1/2	13/16 - 16	0.378	1.13	3/4	9,200
FS-2650-10-10-10-10-4	5/8	1 - 14	0.484	1.31	1 5/8	6,000
FS-2650-12-12-12-12-4	3/4	1 3/16 - 12	0.609	1.48	1 3/16	6,000
FS-2650-16-16-16-16-4	1"	1 7/16 - 12	0.813	1.40	1 7/16	6,000
FS-2650-20-20-20-20-4	1 1/4	1 11/16 - 12	1.024	1.76	1 5/8	5,000

4:1 Safety Factor