


6400R

Restrictor Straight Thread Connector Male JIC x Male ORB

SAE 070120



6400R-①-②-③ ①-MJ ②-MB ③-Orifice	Tube O.D.	① Male JIC	② Male ORB	③ Orifice	C Hex	D Drill	L Length	Operating Pressure
6400R-04-04-.000	1/4	7/16 - 20	7/16 - 20	Blank	9/16	0.172	1.23	7,500
6400R-04-04-.031	1/4	7/16 - 20	7/16 - 20	1/32	9/16	0.172	1.23	7,500
6400R-04-04-.042	1/4	7/16 - 20	7/16 - 20	#58	9/16	0.172	1.23	7,500
6400R-04-04-.062	1/4	7/16 - 20	7/16 - 20	1/16	9/16	0.172	1.23	7,500
6400R-04-06-.031	1/4	7/16 - 20	9/16 - 18	1/32	11/16	0.172	1.29	6,000
6400R-04-06-.042	1/4	7/16 - 20	9/16 - 18	#58	11/16	0.172	1.29	6,000
6400R-04-06-.046	1/4	7/16 - 20	9/16 - 18	#56	11/16	0.172	1.29	6,000
6400R-04-06-.062	1/4	7/16 - 20	9/16 - 18	1/16	11/16	0.172	1.29	6,000
6400R-06-06-.000	3/8	9/16 - 18	9/16 - 18	Blank	11/16	0.297	1.30	6,000
6400R-06-06-.031	3/8	9/16 - 18	9/16 - 18	1/32	11/16	0.297	1.30	6,000
6400R-06-06-.045	3/8	9/16 - 18	9/16 - 18	1.15mm	11/16	0.297	1.30	6,000
6400R-06-06-.052	3/8	9/16 - 18	9/16 - 18	#55	11/16	0.297	1.30	6,000
6400R-06-06-.062	3/8	9/16 - 18	9/16 - 18	1/16	11/16	0.297	1.30	6,000
6400R-06-08-.000	3/8	9/16 - 18	3/4 - 16	Blank	7/8	0.297	1.38	6,000
6400R-06-08-.031	3/8	9/16 - 18	3/4 - 16	1/32	7/8	0.297	1.38	6,000
6400R-06-08-.035	3/8	9/16 - 18	3/4 - 16	#65	7/8	0.297	1.38	6,000
6400R-06-08-.062	3/8	9/16 - 18	3/4 - 16	1/16	7/8	0.297	1.38	6,000
6400R-06-08-.125	3/8	9/16 - 18	3/4 - 16	1/8	7/8	0.297	1.38	6,000
6400R-08-08-.000	1/2	3/4 - 16	3/4 - 16	Blank	7/8	0.391	1.48	6,000
6400R-08-08-.031	1/2	3/4 - 16	3/4 - 16	1/32	7/8	0.391	1.48	6,000
6400R-08-08-.062	1/2	3/4 - 16	3/4 - 16	1/16	7/8	0.391	1.48	6,000

4:1 Safety Factor

O-Ring Boss
Fittings

③ We can also drill the blank restrictor (.000) to your specifications.

③ More **RESTRICTOR** fittings

1404R (pg. 43)	6400R (pg. 134)
1501R (pg. 47)	6801R (pg. 157)
2404R (pg. 70)	6900R (pg. 167)
2406R (pg. 73)	6901R (pg. 169)
5405R (pg. 114)	6902R (pg. 171)