


SAE J514

Ref. Parker F50F
Ref. Weatherhead C3249



6401
Male ORB x Male Pipe

6401-①-② ①-MB ②-MP	① Male ORB	② Male NPTF	C Hex	D Drill	D1 Drill	L Length	Operating Pressure
6401-04-02	7/16 - 20	1/8 - 27	9/16	0.172	0.188	1.04	6,000
6401-04-04	7/16 - 20	1/4 - 18	9/16	0.172	0.281	1.24	6,000
6401-05-02	1/2 - 20	1/8 - 27	5/8	0.188	0.188	1.02	6,000
6401-05-04	1/2 - 20	1/4 - 18	5/8	0.234	0.234	1.20	6,000
6401-06-02	9/16 - 18	1/8 - 27	11/16	0.188	0.188	1.04	6,000
6401-06-04	9/16 - 18	1/4 - 18	11/16	0.297	0.281	1.28	6,000
6401-06-06	9/16 - 18	3/8 - 18	3/4	0.297	0.406	1.22	6,000
6401-06-08	9/16 - 18	1/2 - 14	15/16	0.297	0.531	1.53	6,000
6401-08-04	3/4 - 16	1/4 - 18	7/8	0.391	0.281	1.38	6,000
6401-08-06	3/4 - 16	3/8 - 18	7/8	0.391	0.391	1.36	6,000
6401-08-08	3/4 - 16	1/2 - 14	7/8	0.391	0.391	1.56	6,000
6401-08-12	3/4 - 16	3/4 - 14	1 1/8	0.391	0.391	1.78	5,500
6401-10-06	7/8 - 14	3/8 - 18	1"	0.406	0.406	1.47	6,000
6401-10-08	7/8 - 14	1/2 - 14	1"	0.484	0.484	1.56	6,000
6401-10-12	7/8 - 14	3/4 - 14	1 1/8	0.484	0.719	1.64	5,000
6401-12-06	1 1/16 - 12	3/8 - 18	1 1/8	0.609	0.406	1.55	5,000
6401-12-08	1 1/16 - 12	1/2 - 14	1 1/4	0.609	0.531	1.84	5,000
6401-12-12	1 1/16 - 12	3/4 - 14	1 1/4	0.609	0.719	1.73	5,000
6401-12-16	1 1/16 - 12	1 - 11 1/2	1 3/8	0.609	0.609	2.02	4,500
6401-14-12	1 3/16 - 12	3/4 - 14	1 1/4	0.719	0.609	1.73	4,500
6401-16-12	1 5/16 - 12	3/4 - 14	1 1/2	0.844	0.719	1.95	4,500
6401-16-16	1 5/16 - 12	1 - 11 1/2	1 1/2	0.844	0.844	2.05	4,500
6401-20-20	1 5/8 - 12	1 1/4 - 11 1/2	1 7/8	1.078	1.250	2.18	3,000
6401-24-16	1 7/8 - 12	1 - 11 1/2	2.13	1.312	0.938	2.20	3,000
6401-24-24	1 7/8 - 12	1 1/2 - 11 1/2	2 1/8	1.312	1.500	2.28	2,000
6401-32-32	2 1/2 - 12	2 - 11 1/2	2 3/4	1.781	1.781	2.26	2,000

4:1 Safety Factor

O-Ring Boss
Fittings

Pressure Connections uses **Mandrels** to **Install** our O-rings to prevent the threads from nicking the O-ring.

O-Ring Boss information is on pages 130–131, 155.