


SAE J514

Ref. BRN 3474
 Ref. Parker F50HA0 / 0505
 Ref. Weatherhead C5314



6407
Male ORB Union
MB x MB (Adjustable)

6407-①-② ①-MB ②-MB	① ② Male ORB	C Body Hex	C1 Nut Hex	D Drill	L Length	Operating Pressure
6407-04-04	7/16 - 20	9/16	9/16	0.172	1.46	6,000
6407-06-06	9/16 - 18	11/16	11/16	0.297	1.41	6,000
6407-08-08	3/4 - 16	7/8	7/8	0.391	1.56	6,000
6407-10-10	7/8 - 14	1"	1"	0.484	2.04	5,000
6407-12-12	1 1/16 - 12	1 1/4	1 1/4	0.609	2.34	5,000
6407-16-16	1 5/16 - 12	1 1/2	1 1/2	0.844	2.36	4,000
6407-20-20	1 5/8 - 12	1 7/8	1 7/8	1.078	2.32	4,000
6407-24-24	1 7/8 - 12	2 1/8	2 1/8	1.312	2.42	3,000
6407-32-32	2 1/2 - 12	2 3/4	2 3/4	1.781	2.13	2,000

4:1 Safety Factor

O-Ring Boss information is on pages 130–131, 155.

O-Ring Boss
Fittings

QA Quality Assurance Tips
 We maintain our prints and update our manufacturing processes to the **Latest SAE Standards.**