


SAE 070220

Ref. Aeroquip 2062
 Ref. Parker C50X / 2503
 Ref. Weatherhead C5515



6801
Straight Thread Elbow
Male JIC x Male ORB

Continued from previous page.

6801-①-② ① -MJ ② -MB	Tube O.D.	① Male JIC	② Male ORB	C Nut Hex	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
6801-12-06-4	3/4	1 1/16 - 12	9/16 - 18	11/16	0.609	0.297	1.66	1.49	1 1/16	5,000
6801-12-08-4	3/4	1 1/16 - 12	3/4 - 16	7/8	0.609	0.391	1.66	1.62	1 1/16	5,000
6801-12-10-4	3/4	1 1/16 - 12	7/8 - 14	1"	0.609	0.484	1.66	1.78	1 1/16	5,000
6801-12-12-4	3/4	1 1/16 - 12	1 1/16 - 12	1 1/4	0.609	0.609	1.66	1.94	1 1/16	5,000
6801-12-14	3/4	1 1/16 - 12	1 3/16 - 12	1 3/8	0.609	0.719	1.72	2.00	1 1/4	5,000
6801-12-16-4	3/4	1 1/16 - 12	1 5/16 - 12	1 1/2	0.609	0.839	1.76	2.05	1 5/16	4,000
6801-12-20-4	3/4	1 1/16 - 12	1 5/8 - 12	1 7/8	0.609	1.078	1.97	2.25	1 5/8	4,000
6801-14-14-4	7/8	1 3/16 - 12	1 3/16 - 12	1 3/8	0.719	0.719	1.73	2.00	1 5/16	5,000
6801-16-08-4	1"	1 5/16 - 12	3/4 - 16	7/8	0.844	0.391	1.77	1.71	1 5/16	4,000
6801-16-10-4	1"	1 5/16 - 12	7/8 - 14	1"	0.844	0.484	1.81	1.89	1 5/16	4,000
6801-16-12-4	1"	1 5/16 - 12	1 1/16 - 12	1 1/4	0.844	0.609	1.81	2.05	1 5/16	4,000
6801-16-14-4	1"	1 5/16 - 12	1 3/16 - 12	1 3/8	0.844	0.719	1.81	2.05	1 5/16	4,000
6801-16-16-4	1"	1 5/16 - 12	1 5/16 - 12	1 1/2	0.844	0.844	1.81	2.05	1 5/16	4,000
6801-16-20-4	1"	1 5/16 - 12	1 5/8 - 12	1 7/8	0.844	1.078	2.01	2.25	1 5/8	4,000
6801-20-12-4	1 1/4	1 5/8 - 12	1 1/16 - 12	1 1/4	1.078	0.609	2.06	2.25	1 5/8	4,000
6801-20-16-4	1 1/4	1 5/8 - 12	1 5/16 - 12	1 1/2	1.078	0.839	2.06	2.25	1 5/8	4,000
6801-20-20-4	1 1/4	1 5/8 - 12	1 5/8 - 12	1 7/8	1.078	1.078	2.06	2.25	1 5/8	4,000
6801-20-24-4	1 1/4	1 5/8 - 12	1 7/8 - 12	2 1/8	1.078	1.312	2.20	2.39	1 7/8	3,000
6801-24-20-4	1 1/2	1 7/8 - 12	1 5/8 - 12	1 7/8	1.312	1.078	2.33	2.39	1 7/8	3,000
6801-24-24-4	1 1/2	1 7/8 - 12	1 7/8 - 12	2 1/8	1.312	1.312	2.33	2.39	1 7/8	3,000
6801-32-32-4	2"	2 1/2 - 12	2 1/2 - 12	2 3/4	1.781	1.781	3.06	2.89	2 1/2	2,000
6801R - Restrictor Straight Thread Elbow (1/16" Orifice)										
6801R-06-06-062	3/8	9/16 - 18	9/16 - 18	11/16	0.297	0.297	1.06	1.25	9/16	6,000

4:1 Safety Factor

O-Ring Boss
Fittings

③ We can also drill the blank restrictor (.000) to your specifications.

③ More RESTRICTOR fittings

1404R (pg. 43)	6400R (pg. 134)
1501R (pg. 47)	6801R (pg. 157)
2404R (pg. 70)	6900R (pg. 167)
2406R (pg. 73)	6901R (pg. 169)
5405R (pg. 114)	6902R (pg. 171)