


SAE 070429

Ref. Aeroquip 203003
 Ref. Parker S50X / 253T
 Ref. Weatherhead C5715



6803
ORB Branch Tee

6803-①-②-③ ① -MJ ② -MJ ③ -MB	Tube O.D.	①② Male JIC	③ Male ORB	C Nut Hex	D Drill	M Length	N Length	Y Flats	Operating Pressure
6803-04-04-04-4	1/4	7/16 - 20	7/16 - 20	9/16	0.172	0.89	1.03	7/16	6,000
6803-04-04-06	1/4 x 3/8	7/16 - 20	9/16 - 18	11/16	0.172	0.97	1.25	5/8	6,000
6803-05-05-05-4	5/16	1/2 - 20	1/2 - 20	5/8	0.234	0.97	1.13	9/16	6,000
6803-06-06-06-4	3/8	9/16 - 18	9/16 - 18	11/16	0.297	1.06	1.25	9/16	6,000
6803-06-06-08-4	3/8 x 1/2	9/16 - 18	3/4 - 16	7/8	0.297	1.14	1.45	3/4	6,000
6803-08-08-06	1/2 x 3/8	3/4 - 16	9/16 - 18	11/16	0.297	1.25	1.34	13/16	6,000
6803-08-08-08-4	1/2	3/4 - 16	3/4 - 16	7/8	0.391	1.25	1.45	3/4	6,000
6803-08-08-10	1/2 x 5/8	3/4 - 16	7/8 - 14	1"	0.484	1.31	1.70	15/16	5,000
6803-08-08-12-4	1/2 x 3/4	3/4 - 16	1 1/16 - 12	1 1/4	0.609	1.42	1.94	1 1/16	5,000
6803-10-10-08	5/8 x 1/2	7/8 - 14	3/4 - 16	7/8	0.391	1.45	1.51	15/16	5,000
6803-10-10-10-4	5/8	7/8 - 14	7/8 - 14	1"	0.484	1.45	1.70	7/8	5,000
6803-12-12-10	3/4 x 5/8	1 1/16 - 12	7/8 - 14	1"	0.484	1.66	1.80	1.13	5,000
6803-12-12-12-4	3/4	1 1/16 - 12	1 1/16 - 12	1 1/4	0.609	1.66	1.94	1 1/16	5,000
6803-12-12-16-4	3/4 x 1"	1 1/16 - 12	1 5/16 - 12	1 1/2	0.844	1.76	2.05	1 5/16	4,000
6803-16-16-12-4	1" x 3/4	1 5/16 - 12	1 1/16 - 12	1 1/4	0.609	1.81	2.05	1 5/16	4,000
6803-16-16-16-4	1"	1 5/16 - 12	1 5/16 - 12	1 1/2	0.844	1.81	2.05	1 5/16	4,000
6803-20-20-20-4	1 1/4	1 5/8 - 12	1 5/8 - 12	1 7/8	1.078	2.06	2.25	1 5/8	4,000
6803-24-24-24	1 1/2	1 7/8 - 12	1 7/8 - 12	2 1/8	1.312	2.33	2.39	2"	3,000

4:1 Safety Factor

O-Ring Boss
 Fittings



Pressure Connections provides up to date **Gauge Certifications** as part of our equipment and **Gauge Calibration Program**. We out-source our gauge calibrations to ensure inspection consistency.