


5404 Hex Pipe Nipple



SAE 140137

Ref. Aeroquip 2083
Ref. Parker FF / 0101
Ref. Weatherhead C3069

5404-①-② ①-MP ②-MP	① Male NPTF	② Male NPTF	C Hex	D Drill	D1 Drill	L Length	Operating Pressure
5404-02-02	1/8 - 27	1/8 - 27	7/16	0.188	0.188	1.06	6,000
5404-04-02	1/4 - 18	1/8 - 27	5/8	0.281	0.188	1.26	6,000
5404-04-04	1/4 - 18	1/4 - 18	5/8	0.281	0.281	1.45	6,000
5404-04-04X ①	1/4 - 18	1/4 - 18	5/8	0.281	0.281	1.45	6,000
5404-06-02	3/8 - 18	1/8 - 27	3/4	0.406	0.188	1.26	6,000
5404-06-04	3/8 - 18	1/4 - 18	3/4	0.281	0.281	1.45	6,000
5404-06-04X ①	3/8 - 18	1/4 - 18	3/4	0.281	0.281	1.45	6,000
5404-06-06	3/8 - 18	3/8 - 18	3/4	0.406	0.406	1.45	6,000
5404-06-06X ①	3/8 - 18	3/8 - 18	3/4	0.406	0.406	1.45	6,000
5404-08-04	1/2 - 14	1/4 - 18	7/8	0.531	0.281	1.70	6,000
5404-08-06	1/2 - 14	3/8 - 18	7/8	0.531	0.406	1.70	6,000
5404-08-08	1/2 - 14	1/2 - 14	7/8	0.531	0.531	1.89	6,000
5404-12-02	3/4 - 14	1/8 - 27	1 1/8	0.719	0.188	1.59	6,000
5404-12-04	3/4 - 14	1/4 - 18	1 1/8	0.719	0.281	1.78	5,500
5404-12-06	3/4 - 14	3/8 - 18	1 1/8	0.719	0.406	1.77	5,500
5404-12-08	3/4 - 14	1/2 - 14	1 1/8	0.719	0.531	1.96	5,500
5404-12-12	3/4 - 14	3/4 - 14	1 1/8	0.719	0.719	1.96	5,500
5404-16-08	1 - 11 1/2	1/2 - 14	1 3/8	0.938	0.531	2.09	4,500
5404-16-12	1 - 11 1/2	3/4 - 14	1 3/8	0.938	0.719	2.15	4,500
5404-16-16	1 - 11 1/2	1 - 11 1/2	1 3/8	0.938	0.938	2.34	4,500
5404-20-12	1 1/4 - 11 1/2	3/4 - 14	1 3/4	1.250	0.719	2.26	3,000
5404-20-16	1 1/4 - 11 1/2	1 - 11 1/2	1 3/4	1.250	1.250	2.45	3,000
5404-20-20	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1 3/4	1.250	1.250	2.48	3,000
5404-24-12	1 1/2 - 11 1/2	3/4 - 14	2"	1.500	0.719	2.36	3,000
5404-24-16 ①	1 1/2 - 11 1/2	1 - 11 1/2	2"	1.500	0.938	2.55	3,000
5404-24-20 ①	1 1/2 - 11 1/2	1 1/4 - 11 1/2	2"	1.500	1.250	2.58	3,000
5404-24-24 ①	1 1/2 - 11 1/2	1 1/2 - 11 1/2	2"	1.500	1.500	2.61	3,000
5404-32-16	2 - 11 1/2	1 - 11/12	2 1/2	1.938	0.938	2.73	2,000
5404-32-20	2 - 11 1/2	1 1/4 - 11 1/2	2 1/2	1.780	1.250	2.76	2,000
5404-32-24 ①	2 - 11 1/2	1 1/2 - 11 1/2	2 1/2	1.938	1.500	2.79	2,000
5404-32-32 ①	2 - 11 1/2	2 - 11 1/2	2 1/2	1.938	1.938	2.82	2,000

① These part numbers have a 30° chamfer on both male pipes.

4:1 Safety Factor

Pipe Thread information is on page 106-107.

Pipe
Fittings