


5405

Increase & Extension Connector



SAE 140139

Ref. Aeroquip 2040
Ref. Parker FG / 0201
Ref. Weatherhead C3209


Continued from the previous page.

5405-①-② ① -MP ② -FP	① Male NPTF	② Female NPTF	C Hex	D Drill	L Length	Operating Pressure
5405-16-12	1 - 11 1/2	3/4 - 14	1 3/8	0.938	2.12	3,000
5405-16-16	1 - 11 1/2	1 - 11 1/2	1 5/8	0.938	2.46	3,000
5405-16-20	1 - 11 1/2	1 1/4 - 11 1/2	2"	0.938	2.46	2,500
5405-16-24	1 - 11 1/2	1 1/2 - 11 1/2	2 3/8	0.938	2.54	2,000
5405-20-12	1 1/4 - 11 1/2	3/4 - 14	2"	0.922	1.38	2,500
5405-20-16	1 1/4 - 11 1/2	1 - 11 1/2	2"	1.250	1.91	2,500
5405-20-20	1 1/4 - 11 1/2	1 1/4 - 11 1/2	2"	1.250	2.49	2,500
5405-20-24	1 1/4 - 11 1/2	1 1/2 - 11 1/2	2 3/8	1.250	2.52	2,000
5405-20-32	1 1/4 - 11 1/2	2 - 11 1/2	2 7/8	1.250	2.65	1,500
5405-24-20	1 1/2 - 11 1/2	1 1/4 - 11 1/2	2"	1.500	2.52	2,500
5405-24-24	1 1/2 - 11 1/2	1 1/2 - 11 1/2	2 3/8	1.500	2.53	2,000
5405-24-32	1 1/2 - 11 1/2	2 - 11 1/2	2 7/8	1.500	2.43	1,500
5405-32-32	2 - 11 1/2	2 - 11 1/2	2 7/8	1.938	2.66	1,500

4:1 Safety Factor

5405R

Restrictor Increase & Extension Connector



SAE 140139

5405R-①-②-③ ① -MP ② -FP ③ -Orifice	① Male NPTF	② Female NPTF	③ Orifice	C Hex	L Length	Operating Pressure
5405R-02-02-.025	1/8 - 27	1/8 - 27	# 79	5/8	1.21	6,000
5405R-04-04-.031	1/4 - 18	1/4 - 18	1/32	3/4	1.39	6,000
5405R-04-04-.062	1/4 - 18	1/4 - 18	1/16	3/4	1.39	6,000
5405R-06-06-.000	3/8 - 18	3/8 - 18	BLANK	7/8	1.44	6,000

③ We can also drill the blank restrictor (.000) to your specifications.

4:1 Safety Factor

③ More **RESTRICTOR** fittings

1404R (pg. 43)	6400R (pg. 134)
1501R (pg. 47)	6801R (pg. 157)
2404R (pg. 70)	6900R (pg. 167)
2406R (pg. 73)	6901R (pg. 169)
5405R (pg. 114)	6902R (pg. 171)