


5502

Street Elbow Male x Female Pipe



SAE 140239

Ref. Aeroquip 2089
Ref. Parker CD / 2102
Ref. Weatherhead C3409

5502-①-② ①-MP ②-FP	① Male NPTF	② Female NPTF	D Drill	N Length	N1 Length	Y Flats	Operating Pressure
5502-02-02-4	1/8 - 27	1/8 - 27	0.188	0.78	0.66	9/16	5,000
5502-02-04-4	1/8 - 27	1/4 - 18	0.188	0.90	0.88	3/4	5,000
5502-02-06	1/8 - 27	3/8 - 18	0.188	1.03	1.02	7/8	4,500
5502-04-02-4	1/4 - 18	1/8 - 27	0.281	0.78	0.66	9/16	5,000
5502-04-04-4	1/4 - 18	1/4 - 18	0.281	1.09	0.88	3/4	5,000
5502-04-06-4	1/4 - 18	3/8 - 18	0.281	1.22	1.02	7/8	4,500
5502-06-04-4	3/8 - 18	1/4 - 18	0.406	1.22	0.88	7/8	5,000
5502-06-06-4	3/8 - 18	3/8 - 18	0.406	1.22	1.02	7/8	4,500
5502-06-08-4	3/8 - 18	1/2 - 14	0.406	1.28	1.23	1 1/16	3,000
5502-08-04	1/2 - 14	1/4 - 18	0.531	1.44	0.98	15/16	3,000
5502-08-04-4	1/2 - 14	1/4 - 18	0.531	1.47	1.00	1 1/16	3,000
5502-08-06-4	1/2 - 14	3/8 - 18	0.531	1.47	1.01	1 1/16	4,500
5502-08-08-4	1/2 - 14	1/2 - 14	0.531	1.47	1.23	1 1/16	3,000
5502-08-12-4	1/2 - 14	3/4 - 14	0.531	1.58	1.36	1 1/4	4,500
5502-12-08-4	3/4 - 14	1/2 - 14	0.719	1.59	1.23	1 1/16	3,000
5502-12-12-4	3/4 - 14	3/4 - 14	0.719	1.59	1.36	1 5/16	3,000
5502-12-16-4	3/4 - 14	1 - 11 1/2	0.719	1.61	1.62	1 5/8	2,200
5502-16-12-4	1 - 11 1/2	3/4 - 14	0.938	2.14	1.39	1 5/16	2,200
5502-16-16-4	1 - 11 1/2	1 - 11 1/2	0.938	1.97	1.62	1 5/8	2,200
5502-16-20	1 - 11 1/2	1 1/4 - 11 1/2	0.938	2.35	1.70	1 7/8	1,800
5502-20-16-4	1 1/4 - 11 1/2	1 - 11 1/2	1.250	2.50	1.63	1 5/8	1,800
5502-20-20-4	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1.250	2.38	1.70	1 7/8	1,800
5502-24-24-4	1 1/2 - 11 1/2	1 1/2 - 11 1/2	1.500	2.64	2.08	2 9/16	1,800
5502-32-32-4	2 - 11 1/2	2 - 11 1/2	1.938	3.00	2.39	2 13/16	1,200

4:1 Safety Factor

Pipe
Fittings



Informational Tips

Ask for our **Brass Fittings and Barbs** catalog.