


SAE 514

Ref. Aeroquip 2257
Ref. Parker RRS



5600
Male Pipe Tee


5600-①-②-③ ①-MP ②-MP ③-MP	①②③ Male NPTF	D Drill	N Length	Y Flats	Operating Pressure
5600-02-02-02-4	1/8 - 27	0.188	0.81	7/16	6,000
5600-04-04-04-4	1/4 - 18	0.281	1.09	9/16	6,000
5600-06-06-06-4	3/8 - 18	0.406	1.22	3/4	6,000
5600-08-08-08-4	1/2 - 14	0.531	1.47	7/8	6,000
5600-12-12-12-4	3/4 - 14	0.719	1.59	1 1/16	4,000
5600-16-16-16-4	1 - 11 1/2	0.938	1.97	1 5/16	3,000
5600-20-20-20-4	1 1/4 - 11 1/2	1.250	2.38	1 3/4	2,500

4:1 Safety Factor

Pipe Thread information is on page 106-107.

SAE 514

Ref. Aeroquip 2256



5601
Female Pipe Branch Tee

Pipe
Fittings

5601-①-②-③ ①-MP ②-MP ③-FP	①② Male NPTF	③ Female NPTF	D Drill	N Length	N1 Length	Y Flats	Operating Pressure
5601-02-02-02-4	1/8 - 27	1/8 - 27	0.188	0.78	0.66	9/16	5,000
5601-04-04-04-4	1/4 - 18	1/4 - 18	0.281	1.09	0.88	3/4	5,000
5601-06-06-06-4	3/8 - 18	3/8 - 18	0.406	1.22	1.02	7/8	4,500
5601-08-08-08-4	1/2 - 14	1/2 - 14	0.531	1.47	1.23	1 1/16	3,000
5601-12-12-12-4	3/4 - 14	3/4 - 14	0.719	1.59	1.36	1 5/16	3,000
5601-16-16-16-4	1 - 11 1/2	1 - 11 1/2	0.938	1.97	1.63	1 5/8	1,800
5601-20-20-20-4	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1.250	2.38	1.70	2"	1,500

4:1 Safety Factor