


5602

Street Tee



SAE 140424


Ref. Aeroquip 2092
Ref. Parker MRO / 012T
Ref. Weatherhead C3759

5602-①-②-③ ①-MP ②-FP ③-FP	① Male NPTF	②③ Female NPTF	D Drill	N Length	N1 Length	Y Flats	Operating Pressure
5602-02-02-02-4	1/8 - 27	1/8 - 27	0.188	0.78	0.66	9/16	5,000
5602-04-04-04-4	1/4 - 18	1/4 - 18	0.281	1.09	0.88	3/4	5,000
5602-06-06-06-4	3/8 - 18	3/8 - 18	0.406	1.22	1.02	7/8	4,500
5602-08-08-08-4	1/2 - 14	1/2 - 14	0.531	1.47	1.23	1 1/16	3,000
5602-12-12-12-4	3/4 - 14	3/4 - 14	0.719	1.59	1.38	1 5/16	3,000
5602-16-16-16-4	1 - 11 1/2	1 - 11 1/2	0.938	1.97	1.62	1 5/8	2,200
5602-20-20-20-4	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1.250	2.38	1.70	1 7/8	1,800
5602-24-24-24-4	1 1/2 - 11 1/2	1 1/2 - 11 1/2	1.500	2.64	2.08	2 9/16	1,500
5602-32-32-32	2 - 11 1/2	2 - 11 1/2	1.938	3.00	2.39	2 7/8	1,200

4:1 Safety Factor

5603

Female Pipe Run Tee



SAE J514

Ref. Aeroquip 2093
Ref. Weatherhead C3805

5603-①-②-③ ①-MP ②-FP ③-MP	①③ Male NPTF	② Female NPTF	D Drill	N Length	N1 Length	Y Flats	Operating Pressure
5603-02-02-02-4	1/8 - 27	1/8 - 27	0.188	0.78	0.66	9/16	5,000
5603-04-04-04-4	1/4 - 18	1/4 - 18	0.281	1.09	0.88	3/4	5,000
5603-06-06-06-4	3/8 - 18	3/8 - 18	0.406	1.22	1.02	7/8	4,500
5603-08-08-08-4	1/2 - 14	1/2 - 14	0.531	1.47	1.23	1 1/16	3,000
5603-12-12-12-4	3/4 - 14	3/4 - 14	0.719	1.59	1.38	1 5/16	3,000
5603-16-16-16-4	1 - 11 1/2	1 - 11 1/2	0.938	1.97	1.63	1 5/8	1,800
5603-20-20-20	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1.250	2.38	1.70	2"	1,500
5603-24-24-24	1 1/2 - 11 1/2	1 1/2 - 11 1/2	1.500	2.64	2.08	2 9/16	1,500
5603-24-24-24-4	1 1/2 - 11 1/2	1 1/2 - 11 1/2	1.500	2.64	2.05	2 9/16	1,500

4:1 Safety Factor