


SAE 140425

Ref. Aeroquip 2091
 Ref. Parker MMS / 212T
 Ref. Weatherhead C3609




5604
Male Pipe Branch Tee

5604-①-②-③ ①-FP ②-FP ③-MP	①② Female NPTF	③ Male NPTF	D Drill	N Length	N1 Length	Y Flats	Operating Pressure
5604-02-02-02-4	1/8 - 27	1/8 - 27	0.188	0.88	0.66	9/16	5,000
5604-04-04-04-4	1/4 - 18	1/4 - 18	0.281	1.09	0.88	3/4	5,000
5604-06-06-06-4	3/8 - 18	3/8 - 18	0.406	1.22	1.02	7/8	4,500
5604-08-08-08-4	1/2 - 14	1/2 - 14	0.531	1.47	1.23	1 1/16	3,000
5604-12-12-12-4	3/4 - 14	3/4 - 14	0.719	1.59	1.36	1 5/16	3,000
5604-16-16-16-4	1 - 11 1/2	1 - 11 1/2	0.938	1.97	1.62	1 5/8	1,800
5604-20-20-20-4	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1.250	2.38	1.70	1 7/8	1,500
5604-24-24-24-4	1 1/2 - 11 1/2	1 1/2 - 11 1/2	1.500	2.64	2.08	2 9/16	1,500

4:1 Safety Factor

SAE 140438

Ref. Aeroquip 2090
 Ref. Parker MMO / 022T
 Ref. Weatherhead C3709



5605
Female Pipe Tee

5605-①-②-③ ①-FP ②-FP ③-FP	①②③ Female NPTF	N Length	Y Flats	Operating Pressure
5605-02-02-02-4	1/8 - 27	0.66	9/16	5,000
5605-04-04-04-4	1/4 - 18	0.88	3/4	5,000
5605-06-06-06-4	3/8 - 18	1.02	7/8	4,500
5605-08-08-08-4	1/2 - 14	1.23	1 1/16	3,000
5605-12-12-12-4	3/4 - 14	1.36	1 5/16	3,000
5605-16-16-16-4	1 - 11 1/2	1.62	1 5/8	2,200
5605-20-20-20-4	1 1/4 - 11 1/2	1.70	1 7/8	1,800
5605-24-24-24-4	1 1/2 - 11 1/2	2.08	2 9/16	1,500

4:1 Safety Factor

Pipe Thread information is on page 106-107.

Pipe
Fittings