


SAE J514

Ref. Aeroquip 2250
 Ref. Parker X6EF
 Ref. Weatherhead C5406



6501
Swivel Nut Adapter
 Male Pipe x Female JIC Swivel

6501-①-② ①-MP ②-FJX	Tube O.D.	① Male NPTF	② Female JIC Swivel	C Nut Hex	D Drill	D1 Drill	M Length	N Length	Y Flats	Operating Pressure
6501-02-04-4	1/4	1/8 - 27	7/16 - 20	9/16	0.188	0.172	0.78	1.01	7/16	6,000
6501-04-04-4	1/4	1/4 - 18	7/16 - 20	9/16	0.281	0.172	1.09	1.05	9/16	6,000
6501-04-06-4	3/8	1/4 - 18	9/16 - 18	11/16	0.281	0.297	1.06	1.27	9/16	5,000
6501-06-06-4	3/8	3/8 - 18	9/16 - 18	11/16	0.406	0.297	1.22	1.26	3/4	5,000
6501-06-08-4	1/2	3/8 - 18	3/4 - 16	7/8	0.406	0.391	1.22	1.34	3/4	5,000
6501-08-08-4	1/2	1/2 - 14	3/4 - 16	7/8	0.531	0.391	1.47	1.48	7/8	5,000
6501-08-10-4	5/5	1/2 - 14	7/8 - 14	1"	0.531	0.484	1.47	1.63	7/8	5,000
6501-12-12-4	3/4	3/4 - 14	1 1/16 - 12	1 1/4	0.719	0.609	1.50	1.68	1 1/16	4,000
6501-16-16-4	1"	1 - 11 1/2	1 5/16 - 12	1 1/2	0.938	0.844	1.95	2.09	1 5/16	3,000
6501-20-20-4	1 1/4	1 1/4 - 11 1/2	1 5/8 - 12	2"	1.250	1.078	2.38	2.42	1 5/8	2,500
6501-24-24-4	1 1/2	1 1/2 - 11 1/2	1 7/8 - 12	2 1/4	1.500	1.312	2.64	2.70	1 7/8	2,500
6501-32-32	2"	2 - 11 1/2	2 1/2 - 12	2 7/8	1.938	1.781			2 1/2	1,500

4:1 Safety Factor

Female JIC Swivel information is on page 146.

