


Female JIC Swivels

PRESSURE CONNECTIONS CORP.

6502

Swivel Nut Elbow

Male JIC x Female JIC Swivel



SAE 070321

Ref. Aeroquip 2070
Ref. Parker V6X / 3703
Ref. Weatherhead C5356


6502-①-② ①-MJ ②-FJX	Tube O.D.	① Male JIC	② Female JIC Swivel	C Nut Hex	D Drill	M Length	N Length	Y Flats	Operating Pressure
6502-04-04-4	1/4	7/16 - 20	7/16 - 20	9/16	0.172	0.72	0.94	7/16	7,500
6502-05-05-4	5/16	1/2 - 20	1/2 - 20	5/8	0.234	0.77	1.00	9/16	5,000
6502-06-06-4	3/8	9/6 - 18	9/6 - 18	11/16	0.297	0.83	1.12	9/16	5,000
6502-08-08-4	1/2	3/4 - 16	3/4 - 16	7/8	0.391	0.98	1.28	3/4	5,000
6502-10-10-4	5/8	7/8 - 14	7/8 - 14	1"	0.484	1.11	1.44	7/8	5,000
6502-12-12-4	3/4	1 1/16 - 12	1 1/16 - 12	1 1/4	0.609	1.33	1.50	1 1/16	5,000
6502-14-14	7/8	1 3/16 - 12	1 3/16 - 12	1 3/8	0.719	1.39	1.62	1 1/4	4,000
6502-16-16-4	1"	1 5/16 - 12	1 5/16 - 12	1 1/2	0.844	1.47	1.75	1 5/16	3,600
6502-20-20-4	1 1/4	1 5/8 - 12	1 5/8 - 12	2"	1.078	1.59	2.01	1 5/8	3,600
6502-24-24-4	1 1/2	1 7/8 - 12	1 7/8 - 12	2 1/4	1.312	1.78	2.27	1 7/8	2,500
6502-32-32-4	2"	2 1/2 - 12	2 1/2 - 12	2 7/8	1.781	2.22	2.91	2 1/2	1,500

4:1 Safety Factor

6502BT

Bent Tube Elbow

Male JIC x Female JIC Swivel



SAE J514

Ref. TMP 6702

6502BT-①-② ①-MJ ②-FJX	Tube O.D.	① Male JIC	② Female JIC Swivel	C Body Hex	C1 Nut Hex	L Length	N Length	Operating Pressure
6502BT-04-04	1/4	7/16 - 20	7/16 - 20	1/2	9/16	1.97	0.79	5,000
6502BT-06-06	3/8	9/16 - 18	9/16 - 18	5/8	11/16	2.24	0.98	4,000
6502BT-08-08	1/2	3/4 - 16	3/4 - 16	13/16	7/8	2.56	1.18	3,500
6502BT-10-10	5/8	7/8 - 14	7/8 - 14	15/16	1"	3.03	1.26	2,700
6502BT-12-12	3/4	1 1/16 - 12	1 1/16 - 12	1 1/8	1 1/4	3.54	1.57	2,200
6502BT-16-16	1"	1 5/16 - 12	1 5/16 - 12	1 3/8	1 1/2	4.13	1.77	2,000

4:1 Safety Factor

Female JIC
Swivels