


K2 Series Fittings

Use With 1SN, 2SN, R16-2SC, R17, Pressure Wash, Jack Hose, and R4 Hoses

K21190

Female OFS Swivel 90°

Ref. Parker 1J943 / 1J543



Part No.	1 - Hose Size		2 - Female OFS Sw.	A - Length		B - Cut-Off Allow.		C - Optional Len.		E - Drop Length		W - Nut Hex	
	(in)	(mm)	(in)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
K21190-04-04	1/4	6,4	9/16 - 18	2.01	51,0	1.18	30,0	0.32	8,0	0.95	24,0	11/16	17,4
K21190-04-06	1/4	6,4	11/16 - 16	2.01	51,0	1.18	30,0	0.35	9,0	1.02	26,0	13/16	20,6
K21190-04-08	1/4	6,4	13/16 - 16	2.01	51,0	1.18	30,0	0.43	11,0	1.10	28,0	15/16	23,8
K21190-06-04	3/8	9,5	9/16 - 18	2.72	69,0	1.65	42,0	0.32	8,0	0.99	25,0	11/16	17,4
K21190-06-06	3/8	9,5	11/16 - 16	2.72	69,0	1.65	42,0	0.35	9,0	1.02	26,0	13/16	20,6
K21190-06-08	3/8	9,5	13/16 - 16	2.72	69,0	1.65	42,0	0.43	11,0	1.10	28,0	15/16	23,8
K21190-08-06	1/2	12,7	11/16 - 16	2.76	70,0	1.5	38,0	0.35	9,0	1.10	28,0	13/16	20,6
K21190-08-08	1/2	12,7	13/16 - 16	2.76	70,0	1.5	38,0	0.43	11,0	1.18	30,0	15/16	23,8
K21190-08-10	1/2	12,7	1 - 14	2.76	70,0	1.5	38,0	0.55	14,0	1.22	31,0	1 1/8	28,5
K21190-08-12	1/2	12,7	1 3/16 - 12	2.76	70,0	1.5	38,0	0.59	15,0	1.18	30,0	1 3/8	34,9
K21190-10-08	5/8	15,9	13/16 - 16	2.8	71,0	1.65	42,0	0.43	11,0	1.46	37,0	15/16	23,8
K21190-10-10	5/8	15,9	1 - 14	2.8	71,0	1.65	42,0	0.55	14,0	1.50	38,0	1 1/8	28,5
K21190-10-12	5/8	15,9	1 3/16 - 12	2.8	71,0	1.65	42,0	0.59	15,0	1.46	37,0	1 3/8	34,9
K21190-12-10	3/4	19,1	1 - 14	3.98	101,0	2.4	61,0	0.55	14,0	1.97	50,0	1 1/8	28,5
K21190-12-12	3/4	19,1	1 3/16 - 12	3.98	101,0	2.4	61,0	0.59	15,0	1.93	49,0	1 3/8	34,9
K21190-12-16	3/4	19,1	1 7/16 - 12	3.98	101,0	2.4	61,0	0.63	16,0	1.93	49,0	1 5/8	41,2
K21190-16-12	1"	25,4	1 3/16 - 12	4.96	126,1	3.19	81,0	0.59	15,0	2.25	57,0	1 3/8	34,9
K21190-16-16	1"	25,4	1 7/16 - 12	4.96	126,1	3.19	81,0	0.63	16,0	2.25	57,0	1 5/8	41,2
K21190-16-20	1"	25,4	1 11/16 - 12	4.96	126,1	3.19	81,0	0.63	16,0	2.36	60,0	1 7/8	47,6
K21190-20-16	1 1/4	31,8	1 7/16 - 12	5.52	140,1	3.66	93,0	0.63	16,0	2.92	74,0	1 5/8	41,2
K21190-20-20	1 1/4	31,8	1 11/16 - 12	5.52	140,1	3.66	93,0	0.63	16,0	3.03	77,0	1 7/8	47,6
K21190-20-24	1 1/4	31,8	2 - 12	5.52	140,1	3.66	93,0	0.63	16,0	3.03	77,0	2 1/4	57,1
K21190-24-24	1 1/2	38,1	2 - 12	5.95	151,1	3.59	91,0	0.63	16,0	3.15	80,0	2 1/4	57,1