

EATON 3-R

Special Purpose EATON 3RL Ring-Lock Series


Notable Features:

- Eaton-Hansen Ring-Lock Series
- Pneumatic 3/8" Capacity
- Steel Body and Sleeve, Zinc Plated
- Rotate Sleeve 20° to Disconnect
- Prevents Accidental Disconnection
- High Flow Capacity
- Automatic Push-To-Connect Design
- Buna-N Seals
- -40° to +250° F (-40° to +121° C)
- Seal Options Available
- Page Update: 2015-11-01

The **Eaton 3RL Ring-Lock Series** is a unique interchange designed by Eaton for compressed air applications in shipyards, mining, marine, and general pneumatic service.

EATON 3RL Ring-Lock Coupler

Steel



3-R

Part No.	Flow Size	Thread Size	Thread Type	Thread	Working PSI	Burst PSI	Reference	
							Eaton-Hansen	Foster
3-R16	3/8	1/4	Female	1/4 - 18	300	1,200	3R16	3R4015
3-R21	3/8	3/8	Female	3/8 - 18	300	1,200	3R21	3R5005
3-R26	3/8	1/2	Female	1/2 - 14	300	1,200	3R26	3R5205
3-R31A	3/8	3/4	Female	3/4 - 14	300	1,200	3R31A	3R5405
3-R17	3/8	1/4	Industrial	Barb	300	1,200	3R17	3R5605
3-R195	3/8	5/16	Industrial	Barb	300	1,200	3R195	—
3-R22	3/8	3/8	Industrial	Barb	300	1,200	3R22	3R5705
3-R27	3/8	1/2	Industrial	Barb	300	1,200	3R27	3R5805
3-R32	3/8	3/4	Industrial	Barb	300	1,200	3R32	3R5905
3-R15	3/8	1/4	Male	1/4 - 18	300	1,200	3R15	3R4905
3-R20	3/8	3/8	Male	3/8 - 18	300	1,200	3R20	3R5105
3-R25	3/8	1/2	Male	1/2 - 14	300	1,200	3R25	3R5305
3-R30	3/8	3/4	Male	3/4 - 14	300	1,200	3R30	3R5505

Crossover references Do Not necessarily match All attributes of the series shown.

