

Solid Bottom Valves

Features:

- Good for Water, Fuel Oil, Gas, Air, and LP Gas
- Brass Body
- Steel "Pointer" Lever Handle
- Solid Bottom, Spring Loaded Top
- Neoprene O-Ring Seal Prevents Leakage To/From the Atmosphere
- Packed with NON-Drying Synthetic Grease
- Quick 90° On/Off Operation With a 360° Rotation
- Use With Copper, Aluminum, Steel, and Plastic Tubing

SBV-3200

FP x MP - Brass



Part No.	Female Pipe	Male Pipe	Pressure
SBV-3200-02-02	1/8 - 27	1/8 - 27	30 PSI
SBV-3200-04-04	1/4 - 18	1/4 - 18	30 PSI

SBV-3300

FP x FP - Brass



Part No.	Female Pipe	Female Pipe	Pressure
SBV-3300-04-04	1/4 - 18	1/4 - 18	30 PSI

SBV-3700

FP x FP x FP - 3-Way - Brass



Part No.	Female Pipe	Female Pipe	Pressure
SBV-3700-04-04-04	1/4 - 18	1/4 - 18	30 PSI
SBV-3700-06-06-06	3/8 - 18	3/8 - 18	30 PSI

- Handle Clicks at Each 90° Increment
- Greaseless Non-Lubricated Design
- Relubrication NOT Required
- Panel Mount Holes
- NOT for LP Gas
- **Temperature**
-40° to +180° F (-40° to +82° C)