

# EATON 600


## Gas, Oxygen, Acetylene EATON 600 Series

### Notable Features:

- Eaton-Hansen 600 Series
- Oxygen Coupling Prevents Crossing with Acetylene Lines
- OSHA Compliant
- GREEN Color Coded Sleeve
- 1/4" Capacity
- Brass Construction
- Buna-N Seals
- -40° to +250° F (-40° to +121° C)
- Page Update: 2015-11-01

The **Eaton-Hansen 600 and 700 Series Brass** couplings are designed for use with Oxygen and Acetylene applications, but can be used with compressed air and other gases. They are functionally identical, but **Do NOT** interchange, plus they have color coded sleeves (Oxygen-GREEN / Acetylene-RED) to avoid crossing lines. Applications include: Breathing Equipment, Welding, Shipyards, Construction, Nitous Oxide, and General Pneumatics.

## EATON 600 Series Coupler Oxygen Green - Brass



GR

GR-SL

### GR

Part No.	Flow Size	Thread Size	Thread Type	Thread	Working PSI	Burst PSI	Reference	
							Eaton-Hansen	Foster
GR-600	1/4	1/8	Female	1/8 - 27	1,500	6,000	GR600	0-2803
GR-602	1/4	1/4	Female	1/4 - 18	1,500	6,000	GR602	0-3003
GR-604	1/4	3/8	Female	3/8 - 18	1,500	6,000	GR604	0-3203
GR-605R	1/4	9/16	Female	9/16 - 18	1,500	6,000	GR605R	—
GR-604R	1/4	9/16	Male	9/16 - 18	1,500	6,000	GR604R	—
GR-606	1/4	1/4	Industrial	Barb	1,500	6,000	GR606	0-3603
GR-607	1/4	5/16	Industrial	Barb	1,500	6,000	GR607	0-3653
GR-608	1/4	3/8	Industrial	Barb	1,500	6,000	GR608	0-3703
GR-606P	1/4	1/4	Push-Lock	Barb	1,500	6,000	GR606P	0-1513
GR-608P	1/4	3/8	Push-Lock	Barb	1,500	6,000	GR608P	0-1713
GR-601	1/4	1/8	Male	1/8 - 27	1,500	6,000	GR601	0-2903
GR-603	1/4	1/4	Male	1/4 - 18	1,500	6,000	GR603	0-3103
GR-605	1/4	3/8	Male	3/8 - 18	1,500	6,000	GR605	0-3303

### GR Sleeve Lock

Part No.	Flow Size	Thread Size	Thread Type	Thread	Working PSI	Burst PSI	Reference	
							Eaton-Hansen	Foster
GR-602-SL	1/4	1/4	Female	1/4 - 18	1,500	6,000	GR602-SL	BLO-3003
GR-604-SL	1/4	3/8	Female	3/8 - 18	1,500	6,000	GR604-SL	BLO-3203
GR-605R-SL	1/4	9/16	Female	9/16 - 18	1,500	6,000	GR605R-SL	—
GR-604R-SL	1/4	9/16	Male	9/16 - 18	1,500	6,000	GR604R-SL	—
GR-606-SL	1/4	1/4	Industrial	Barb	1,500	6,000	GR606-SL	BLO-3603
GR-607-SL	1/4	5/16	Industrial	Barb	1,500	6,000	GR607-SL	BLO-3653
GR-608-SL	1/4	3/8	Industrial	Barb	1,500	6,000	GR608-SL	BLO-3703
GR-606P-SL	1/4	1/4	Push-Lock	Barb	1,500	6,000	GR606P-SL	BLO-1513
GR-603-SL	1/4	1/4	Male	1/4 - 18	1,500	6,000	GR603-SL	BLO-3103