

PL-250-T

Push-Lock Hose *Flex-Loc*® Push-Lock Hose



Black, Blue, Gray, Green, Red, and Yellow Covers

Part No.	Nominal		I.D.		O.D.		Working Pressure		Bend Radius		Weight		Hose Fitting Series
	(in)	(DN)	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(in)	(mm)	(lbs/ft)	(kg/m)	
PL-BLK-250-04T	1/4	6	0.25	6.4	0.50	12.7	250	17	1.50	38	0.09	0.13	Push-Lock Barbs
PL-BLK-250-06T	3/8	10	0.37	9.5	0.63	15.9	250	17	2.25	57	0.12	0.18	Push-Lock Barbs
PL-BLK-250-08T	1/2	12	0.50	12.7	0.75	19.1	250	17	3.00	76	0.16	0.24	Push-Lock Barbs
PL-BLK-250-10T	5/8	16	0.63	15.9	0.91	23.0	250	17	3.75	95	0.22	0.33	Push-Lock Barbs
PL-BLK-250-12T	3/4	19	0.75	19.0	1.03	26.2	250	17	4.50	114	0.25	0.37	Push-Lock Barbs
PL-BLU-250-04T	1/4	6	0.25	6.4	0.50	12.7	250	17	1.50	38	0.09	0.13	Push-Lock Barbs
PL-BLU-250-06T	3/8	10	0.37	9.5	0.63	15.9	250	17	2.25	57	0.12	0.18	Push-Lock Barbs
PL-BLU-250-08T	1/2	12	0.50	12.7	0.75	19.1	250	17	3.00	76	0.16	0.24	Push-Lock Barbs
PL-RED-250-04T	1/4	6	0.25	6.4	0.50	12.7	250	17	1.50	38	0.09	0.13	Push-Lock Barbs
PL-RED-250-06T	3/8	10	0.37	9.5	0.63	15.9	250	17	2.25	57	0.12	0.18	Push-Lock Barbs
PL-RED-250-08T	1/2	12	0.50	12.7	0.75	19.1	250	17	3.00	76	0.16	0.24	Push-Lock Barbs

DO NOT Use Clamps with Push-Lock Hose Barbs as it Adversely Affects the Holding Capability of the Hose Barb.

Applications/Features

Our 'PL-250-T' *Flex-Loc*® Hose is state-of-the-art in **Push-Lock** Hose. This hose provides superior barb retention while allowing Push-Lock hose barbs to be inserted quickly and easily. This is created by a unique design of spiral yarn and polyester reinforcement that firmly grips the Push-Lock hose barb. No clamps or crimps are needed. *Flex-Loc*® hose has a smooth cover and is a high oil resistant, non-conductive Push-Lock Hose that provides safe performance in harsh, oily conditions. It is ideal for industrial and warehouse applications, or any application where a convenient Push-Lock Hose Barb is needed, but it is NOT recommended for unleaded gasoline. Black, Blue, Gray, Green, Red and Yellow covers available.

Temperature

-20° to +180° F (-29° to +82° C)

Tube

Abrasion Resistant Nitrile, RMA Class A

Notice

Not Recommended for Unleaded Gasoline
For Average Reel Lengths See Page C-150
Push-Lock Hose Barbs on Page B-137
Hose Assemblies or Bulk
Page Updated 2017-02-01

Reinforcement

1-Fiber Spiral Aramid Yarn

Cover

Nitrile/PVC RMA Class A
Black, Blue, Gray, Green, Red, and Yellow

Push-Lock Hose Barbs

272, 27290, 273, 274, 278, 280, 282, 284, 286, 287, 288
290, 292, 294, 294

Reference

Aeroquip-Eaton: 2556, 2565, 2575, FC647, FC3323
Parker: 801, 804, 821, 831
Weatherhead-Eaton: H100, H101, H201

® Registered Trademark of HBD/Thermoid.

Extreme Caution

User is Solely Responsible for the Proper Selection and Matching of Hose and Fitting Components.
Please read the *User Responsibility Warning*, *Hose Installation Guide*, and reference the latest
Crimp Specs at pressureconnections.com.