

PSD-150

Petroleum / Fuel Hose

150 PSI Nitrile Petroleum Suction Hose



Black Cover - Black Characters - Red Stripe

Part Number	I.D.		O.D.		Working Pressure		Bend Radius		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(in)	(mm)	(lbs/ft)	(kg/m)
PSD-150-0075-100	3/4	19,05	1.14	28,96	150	10.35	4.00	101,6	0.36	0,54
PSD-150-0100-100	1"	25,4	1.38	35,0	150	10.35	6.00	152,4	0.49	0,73
PSD-150-0125-100	1-1/4	31,75	1.69	42,93	150	10.35	6.00	152,4	0.81	1,21
PSD-150-0150-100	1-1/2	38,1	2.00	50,8	150	10.35	6.50	165,1	0.91	1,35
PSD-150-0200-100	2"	50,8	2.52	64,01	150	10.35	8.00	203,2	1.14	1,7
PSD-150-0200-200	2"	50,8	2.52	64,01	150	10.35	8.00	203,2	1.14	1,7
PSD-150-0250-100	2-1/2	63,5	3.06	77,72	150	10.35	12.00	304,8	1.76	2,62
PSD-150-0300-100	3"	76,2	3.54	89,92	150	10.35	16.00	406,4	2.42	3,6
PSD-150-0300-200	3"	76,2	3.54	89,92	150	10.35	16.00	406,4	2.42	3,6
PSD-150-0400-100	4"	101,6	4.60	116,84	150	10.35	18.00	457,2	2.69	4,0
PSD-150-0400-200	4"	101,6	4.60	116,84	150	10.35	18.00	457,2	2.69	4,0
PSD-150-0600-020	6"	152,4	6.86	174,24	150	10.35	30.00	762,0	6.28	9,35
PSD-150-0600-100	6"	152,4	6.86	174,24	150	10.35	30.00	762,0	6.28	9,35
PSD-150-0800-020	8"	203,2	8.90	226,06	150	10.35	48.00	1219,2	7.12	10,6
PSD-150-0800-050	8"	203,2	8.90	226,06	150	10.35	48.00	1219,2	7.12	10,6

Applications

For suction or discharge of petroleum-based products in truck and car operations.

Features

Smooth, highly oil resistant tube to handle gasoline and other petroleum products having an aromatic content of 50%. Increased flexibility due to the dual wire helix.

Temperature

-25° F (-32° C) to +200° F (+93° C)

Vacuum Rating

All Sizes Are Full Vacuum

Tube

Nitrile, Black, Smooth ARPM Class A, Highly Oil Resistant

Reinforcement

Synthetic Fabric with Double Wire Helix

Cover

CR, ARPM Class B, Black w/ Red Mylar Stripe

Marking

4420 Petroleum Suction WP 150 PSI 10.35 BAR

Standard Length(s)

All Sizes 100 Feet

2" - 4" 200 Feet