LFH-BLU

Water Hose

PVC Water Discharge Hose - Blue



Blue Cover - Yellow Characters

Part Number	I.D.		O.D.		Working Pressure		Bend Radius		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(in)	(mm)	(lbs/ft)	(kg/m)
LFH-BLU-1000	1"	25,4	0.056	1,42	85	5.86	n/a	n/a	0.10	0,15
LFH-BLU-1500	1-1/2	38,1	0.056	1,42	85	5.86	n/a	n/a	0.21	0,31
LFH-BLU-1500-050	1-1/2	38,1	0.056	1,42	85	5.86	n/a	n/a	0.21	0,31
LFH-BLU-2000	2"	50,8	0.056	1,42	85	5.86	n/a	n/a	0.25	0,37
LFH-BLU-2000-050	2"	50,8	0.056	1,42	85	5.86	n/a	n/a	0.25	0,37
LFH-BLU-2500	2-1/2	63,5	0.060	1,52	75	5.17	n/a	n/a	0.29	0,43
LFH-BLU-3000	3"	76,2	0.062	1,57	70	4.83	n/a	n/a	0.39	0,58
LFH-BLU-3000-050	3"	76,2	0.062	1,57	70	4.83	n/a	n/a	0.39	0,58
LFH-BLU-4000	4"	101,6	0.062	1,57	70	4.83	n/a	n/a	0.60	0,89
LFH-BLU-6000	6"	152,4	0.077	1,96	50	3.45	n/a	n/a	1.15	1,71
LFH-BLU-8000	8"	203,2	0.089	2,26	45	3.1	n/a	n/a	1.20	1,79

Applications
For general purpose water discharge in construction, agriculture, and drip irrigation.

Features
This Layflat Hose is light and easy to handle, rolls flat for storage, and has a homogeneous construction that eliminates tube and cover separation. Reinforced with polyester yarn. Both tube and cover are extruded simultaneously to achieve maximum bonding.

Temperature
–14° F (–26° C) to +150° F (+66° C)

Fittings and Clamps
Anti-Leak Cam-Lock Fittings on Page B-77
Strainers on Page B-119

Tube
PVC, Blue

Reinforcement
Polyester Yarn

Cover
PVC, Blue

Marking
WP XX (PSI) ID

Standard Length(s)
All Sizes 300 Feet
1-1/2", 2", 3" 50 Feet