


K20645

Female JIC Swivel 45°

Ref. Parker 13743 / 1L743



Part No.	1 - Hose Size		2 - Female JIC Sw.	A - Length		B - Cut-Off Allow.		C - Optional Len.		E - Drop Length		W - Nut Hex	
	(in)	(mm)		(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
K20645-04-04	1/4	6,4	7/16 - 20	2.17	55,0	1.34	34,0	0.34	8,7	0.51	13,0	9/16	14,2
K20645-04-05	1/4	6,4	1/2 - 20	2.17	55,0	1.34	34,0	0.37	9,5	0.51	13,0	11/16	17,4
K20645-04-06	1/4	6,4	9/16 - 18	2.21	56,0	1.38	35,0	0.37	9,5	0.55	14,0	11/16	17,4
K20645-06-06	3/8	9,5	9/16 - 18	2.68	68,0	1.62	41,0	0.37	9,5	0.63	16,0	11/16	17,4
K20645-06-08	3/8	9,5	3/4 - 16	2.68	68,0	1.62	41,0	0.42	10,7	0.63	16,0	7/8	22,2
K20645-08-08	1/2	12,7	3/4 - 16	3.15	80,0	1.89	48,0	0.42	10,7	0.75	19,0	7/8	22,2
K20645-08-10	1/2	12,7	7/8 - 14	3.15	80,0	1.89	48,0	0.50	12,7	0.75	19,0	1"	25,4
K20645-10-10	5/8	15,9	7/8 - 14	3.55	90,0	2.01	51,0	0.50	12,7	0.75	19,0	1"	25,4
K20645-10-12	5/8	15,9	1 1/16 - 12	3.55	90,0	2.01	51,0	0.56	14,3	0.75	19,0	1 1/4	31,7
K20645-12-12	3/4	19,1	1 1/16 - 12	4.45	113,1	2.88	73,0	0.56	14,3	1.02	26,0	1 1/4	31,7
K20645-16-16	1"	25,4	1 5/16 - 12	4.81	122,1	3.03	77,0	0.59	15,1	1.22	31,0	1 1/2	38,1
K20645-20-20	1 1/4	31,8	1 5/8 - 12	5.91	150,1	4.06	103,0	0.63	15,9	1.58	40,0	2"	50,8
K20645-24-24	1 1/2	38,1	1 7/8 - 12	6.9	175,1	4.53	115,0	0.73	18,6	1.81	46,0	2 1/8	53,9
K20645-32-32	2"	50,8	2 1/2 - 12	8.31	211,2	5.51	140,0	0.94	23,8	2.44	62,0	2 7/8	73,0