

Nickel Plated Brass

Features:

- Suitable for Air, Water, Oil, and Gas
- Good for Vacuum Service
- 1/4 Turn Open/Close Operation
- Chrome Plated Brass Body
- Chrome Plated Brass Ball
- Nickel Plated Brass Stem
- Composite Handle
- NPTF Thread Ends
- Teflon® Ball Retainer Seal
- Buna-N Stem Seals
- NOT Lead-Free Compliant
- Temperature
–0° to +175° F (–18° to +80° C)

MBV-30102N

MP x FP - Nickel Plated Brass



Part No.	Male Pipe	Female Pipe	Pressure	Body Length	Handle Height	Handle Length	Drill Dia.	Assembly	Body Hex
MBV-30102N-02	1/8 - 27	1/8 - 27	290 PSI	1.48	0.83	0.75	0.22	0.34	0.55
MBV-30102N-04	1/4 - 18	1/4 - 18	290 PSI	1.81	0.83	0.75	0.22	0.51	0.55
MBV-30102N-06	3/8 - 18	3/8 - 18	290 PSI	1.91	0.87	0.75	0.32	0.51	0.71
MBV-30102N-08	1/2 - 14	1/2 - 14	290 PSI	2.44	1.20	1.02	0.39	0.67	0.87

MBV-30202N

FP x FP - Nickel Plated Brass



Part No.	Female Pipe	Female Pipe	Pressure	Body Length	Handle Height	Handle Length	Drill Dia.	Body Hex
MBV-30202N-02	1/8 - 27	1/8 - 27	290 PSI	1.48	0.83	0.75	0.22	0.55
MBV-30202N-04	1/4 - 18	1/4 - 18	290 PSI	1.81	0.83	0.75	0.22	0.55
MBV-30202N-06	3/8 - 18	3/8 - 18	290 PSI	1.91	0.87	0.75	0.32	0.71
MBV-30202N-08	1/2 - 14	1/2 - 14	290 PSI	2.44	1.20	1.02	0.39	0.87

MBV-3020290N

FP x FP 90° - Nickel Plated Brass



Part No.	Female Pipe	Female Pipe	Pressure	Body Length	Body Height	Handle Height	Handle Length	Drill Dia.	Body Hex	Stem Hex
MBV-3020290N-02	1/8 - 27	1/8 - 27	290 PSI	1.48	0.65	1.32	0.75	0.22	0.67	0.67
MBV-3020290N-04	1/4 - 18	1/4 - 18	290 PSI	1.48	0.65	1.32	0.75	0.22	0.67	0.67
MBV-3020290N-06	3/8 - 18	3/8 - 18	290 PSI	1.54	0.87	1.38	0.75	0.28	0.83	0.67

Teflon® is a DuPont Registered Trademark.