



GP-FS2406

SAE J1453

**Female OFS Swivel x Male OFS
Pipe Port**

Continued from previous page.

GP-FS2406-①-②-③P ①-FOFX ②-OFS ③-Pipe Port	Tube O.D.	① Female OFS Swivel	② Male OFS	③ NPTF Port	C Nut Hex	D Drill	L Length	Operating Pressure
GP-FS2406-04-04-2P	1/4	9/16 - 18	9/16 - 18	1/8 - 27	11/16	0.172	2.07	6,000
GP-FS2406-04-04-4P	1/4	9/16 - 18	9/16 - 18	1/4 - 18	11/16	0.172	2.07	6,000
GP-FS2406-04-04-6P	1/4	9/16 - 18	9/16 - 18	3/8 - 18	11/16	0.172	2.07	6,000
GP-FS2406-06-06-2P	3/8	11/16 - 16	11/16 - 16	1/8 - 27	13/16	0.264	2.50	6,000
GP-FS2406-06-06-4P	3/8	11/16 - 16	11/16 - 16	1/4 - 18	13/16	0.264	2.50	6,000
GP-FS2406-06-06-6P	3/8	11/16 - 16	11/16 - 16	3/8 - 18	13/16	0.264	2.50	6,000
GP-FS2406-08-08-2P	1/2	13/16 - 16	13/16 - 16	1/8 - 27	15/16	0.378	2.41	6,000
GP-FS2406-08-08-4P	1/2	13/16 - 16	13/16 - 16	1/4 - 18	15/16	0.378	2.41	6,000
GP-FS2406-08-08-6P	1/2	13/16 - 16	13/16 - 16	3/8 - 18	15/16	0.378	2.41	6,000
GP-FS2406-10-10-2P	5/8	1 - 14	1 - 14	1/8 - 27	1 1/8	0.484	3.54	6,000
GP-FS2406-10-10-4P	5/8	1 - 14	1 - 14	1/4 - 18	1 1/8	0.484	3.54	6,000
GP-FS2406-10-10-6P	5/8	1 - 14	1 - 14	3/8 - 18	1 1/8	0.484	3.54	6,000
GP-FS2406-12-12-2P	3/4	1 3/16 - 12	1 3/16 - 12	1/8 - 27	1 3/8	0.609	4.08	6,000
GP-FS2406-12-12-4P	3/4	1 3/16 - 12	1 3/16 - 12	1/4 - 18	1 3/8	0.609	4.08	6,000
GP-FS2406-12-12-6P	3/4	1 3/16 - 12	1 3/16 - 12	3/8 - 18	1 3/8	0.609	4.08	6,000
GP-FS2406-16-16-2P	1"	1 7/16 - 12	1 7/16 - 12	1/8 - 27	1 5/8	0.811	4.29	6,000
GP-FS2406-16-16-4P	1"	1 7/16 - 12	1 7/16 - 12	1/4 - 18	1 5/8	0.811	4.29	6,000
GP-FS2406-16-16-6P	1"	1 7/16 - 12	1 7/16 - 12	3/8 - 18	1 5/8	0.811	4.29	6,000
GP-FS2406-20-20-2P	1 1/4	1 11/16 - 12	1 11/16 - 12	1/8 - 27	1 7/8	1.024	3.80	4,000
GP-FS2406-20-20-4P	1 1/4	1 11/16 - 12	1 11/16 - 12	1/4 - 18	1 7/8	1.024	3.80	4,000
GP-FS2406-20-20-6P	1 1/4	1 11/16 - 12	1 11/16 - 12	3/8 - 18	1 7/8	1.024	3.80	4,000

4:1 Safety Factor

Gageport Series information is on pages 13-14.