

BV-60202R-LH

Features:

- Suitable for Water, Oil, and Gas
- Saturated Steam 100 PSI
- 1/4 Turn Open/Close Operation
- Standard (Reduced) Port
- 316 Stainless Body, Ball, and Stem
- Blow-Out Proof Stem
- R-PTFE Joint Gasket, Thrust Washer, and Seats
- Insulated Locking Handle
- NPT Pipe Threads

FP x FP - Standard Port - Stainless 316



Part No.	Female Pipe	Female Pipe	WOG	Body Length	Handle Height	Handle Length	Drill Dia.
BV-60202R-LH-04	1/4 - 18	1/4 - 18	800 PSI	1.57	1.32	2.76	0.20
BV-60202R-LH-06	3/8 - 18	3/8 - 18	800 PSI	1.77	1.38	2.76	0.28
BV-60202R-LH-08	1/2 - 14	1/2 - 14	800 PSI	2.17	1.54	3.15	0.35
BV-60202R-LH-12	3/4 - 14	3/4 - 14	800 PSI	2.36	1.93	3.74	0.45
BV-60202R-LH-16	1 - 11 1/2	1 - 11 1/2	800 PSI	2.76	2.13	4.13	0.59
BV-60202R-LH-20	1 1/4 - 11 1/2	1 1/4 - 11 1/2	800 PSI	3.15	2.58	4.72	0.77
BV-60202R-LH-24	1 1/2 - 11 1/2	1 1/2 - 11 1/2	800 PSI	3.39	2.83	5.51	0.98
BV-60202R-LH-32	2 - 11 1/2	2 - 11 1/2	800 PSI	3.98	3.19	5.91	1.26

Applications

Our **BV-60202R-LH Ball Valve** is suitable for water, oil, gas, and steam. It is a durable 316 stainless steel body design with an insulated locking handle that opens and closes the valve with a 90° quarter turn operation. This valve has a Standard port, 316 stainless steel ball, and a 316 stainless steel stem for superior corrosion resistance.

Standard Port Ball Valves, also known as Reduced Port Ball Valves, have a compact ball compared to a full port ball valve, and therefore a smaller orifice that is one pipe size smaller than the threads on the ball valve itself.

Temperature

-20° to +450° F (-28° to +232° C)