Nickel Plated Brass

Features:

- 3 PSI Cracking Pressure
- Nickel Plated Brass Body
- Nickel Plated Brass Piston
- Buna / Viton® Piston Seal
- Steel Spring
- One-Way Flow
- NOT Lead-Free Compliant
- Pressure Range: 3 – 120 PSI
- **Temperature**
  –0° to +160° F (–18° to +71° C)

CV-30101N-3

MP x MP - 3 PSI Crack - Nickel Plated Brass



Part No.	Male Pipe	Male Pipe	Pressure	Length	Assembly	Hex
CV-30101N-04-3	1/4 - 18	1/4 - 18	150 PSI	1.22	0.51	0.55
CV-30101N-06-3	3/8 - 18	3/8 - 18	150 PSI	1.22	0.51	0.75

CV-30202N-3

FP x FP - 3 PSI Crack - Nickel Plated Brass



Part No.	Female Pipe	Female Pipe	Pressure	Length	Hex
CV-30202N-02-3	1/8 - 27	1/8 - 27	150 PSI	1.44	0.51
CV-30202N-04-3	1/4 - 18	1/4 - 18	150 PSI	1.85	0.67

CV-31616N-3

PTC x PTC - 3 PSI Crack - Nickel Plated Brass



Part No.	Push-To-Connect	Push-To-Connect	Pressure	Length	Diameter
CV-31616N-04-3	1/4" Tube	1/4" Tube	150 PSI	2.05	0.51
CV-31616N-06-3	3/8" Tube	3/8" Tube	150 PSI	2.24	0.67

Viton® are DuPont Registered Trademarks.