

924SD

Petroleum / Fuel Hose Type 924 Petroleum Transfer



Black Cover - Black Characters - Red Stripe

Part Number	I.D.		O.D.		Working Pressure		Bend Radius		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(in)	(mm)	(lbs/ft)	(kg/m)
924SD-0100	1"	25,4	1.50	38,1	200	13.79	2.50	63,5	0.50	0,74
924SD-0125	1-1/4	31,75	1.75	44,45	200	13.79	3.00	76,2	0.70	1,04
924SD-0150	1-1/2	38,1	2.00	50,8	150	10.34	4.50	114,3	0.80	1,19
924SD-0200	2"	50,8	2.47	62,71	150	10.34	6.00	152,4	1.00	1,49
924SD-0250	2-1/2	63,5	3.06	77,79	150	10.34	7.50	190,5	1.50	2,23
924SD-0300	3"	76,2	3.56	90,49	150	10.34	9.00	228,6	1.70	2,53
924SD-0400	4"	101,6	4.63	117,48	150	10.34	12.00	304,8	2.50	3,72
924SD-0600	6"	152,4	6.75	171,45	100	6.89	30.00	762,0	5.00	7,44

Applications

Handles fats, greases, animal oils, vegetable oils, hydraulic fluids, and most hydrocarbons with aromatic content up to 55% maximum.

Features

Type 924SD Hose is perfect for bulk transfer applications of petroleum products. The black NBR tube has excellent oil resistances and the NBR/PVC cover is both abrasion and oil resistant.

Temperature

-30° F to +200° F (-34° C to +93° C)

Vacuum Rating

All Sizes Are Full Vacuum

Notice

High oil resistance.

Tube

NBR, RMA Class A, Oil Resistant

Reinforcement

Spiral Steel Wire Helixes Between Synthetic Textile Plies

Cover

NBR/PVC, RMA Class B, Abrasion, Oil Resistant

Marking

Thermoid HBD industries inc. Type 924 Petroleum Transfer WP

Made in USA

Standard Length(s)

100 Feet Max