

EATON 2-R

Special Purpose EATON 2RL Ring-Lock Series


Notable Features:

- Eaton-Hansen Ring-Lock Series
- Pneumatic 1/4" Capacity
- Steel Body and Sleeve, Zinc Plated
- Rotate Sleeve 20° to Disconnect
- Prevents Accidental Disconnection
- High Flow Capacity
- Automatic Push-To-Connect Design
- Buna-N Seals
- -40° to +250° F (-40° to +121° C)
- Seal Options Available
- Page Update: 2015-11-01

The **Eaton 2RL Ring-Lock Series** is a unique interchange designed by Eaton for compressed air applications in shipyards, mining, marine, and general pneumatic service.

EATON 2RL Ring-Lock Coupler

Steel



Part No.	Flow Size	Thread Size	Thread Type	Thread	Working PSI	Burst PSI	Reference	
							Eaton-Hansen	Foster
2-R11	1/4	1/8	Female	1/8 - 27	300	1,200	2R11	—
2-R16	1/4	1/4	Female	1/4 - 18	300	1,200	2R16	2R4404
2-R21	1/4	3/8	Female	3/8 - 18	300	1,200	2R21	2R4204
2-R26	1/4	1/2	Female	1/2 - 14	300	1,200	2R26	2R4404
2-R17	1/4	1/4	Industrial	Barb	300	1,200	2R17	2R4604
2-R195	1/4	5/16	Industrial	Barb	300	1,200	2R195	2R4704
2-R22	1/4	3/8	Industrial	Barb	300	1,200	2R22	2R4804
2-R27	1/4	1/2	Industrial	Barb	300	1,200	2R27	2R4904
2-R10	1/4	1/8	Male	1/8 - 27	300	1,200	2R10	—
2-R15	1/4	1/4	Male	1/4 - 18	300	1,200	2R15	2R4104
2-R20	1/4	3/8	Male	3/8 - 18	300	1,200	2R20	2R4304
2-R25	1/4	1/2	Male	1/2 - 14	300	1,200	2R25	2R4504



Crossover references Do Not necessarily match All attributes of the series shown.