


K21145

Female OFS Swivel 45°

Ref. Parker 1J743



Part No.	1 - Hose Size		2 - Female OFS Sw.	A - Length		B - Cut-Off Allow.		C - Optional Len.		E - Drop Length		W - Nut Hex	
	(in)	(mm)	(in)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
K21145-04-04	1/4	6,4	9/16 - 18	2.17	55,0	1.34	34,0	0.32	8,0	0.51	13,0	11/16	17,4
K21145-04-06	1/4	6,4	11/16 - 16	2.21	56,0	1.38	35,0	0.35	9,0	0.55	14,0	13/16	20,6
K21145-04-08	1/4	6,4	13/16 - 16	2.29	58,0	1.46	37,0	0.43	11,0	0.63	16,0	15/16	23,8
K21145-06-04	3/8	9,5	9/16 - 18	2.64	67,0	1.58	40,0	0.32	8,0	0.59	15,0	11/16	17,4
K21145-06-06	3/8	9,5	11/16 - 16	2.68	68,0	1.62	41,0	0.35	9,0	0.63	16,0	13/16	20,6
K21145-08-06	1/2	12,7	13/16 - 16	3.23	82,0	1.97	50,0	0.43	11,0	0.83	21,0	15/16	23,8
K21145-08-08	1/2	12,7	13/16 - 16	3.23	82,0	1.97	50,0	0.43	11,0	0.83	21,0	1 1/8	28,5
K21145-08-10	1/2	12,7	1 - 14	3.27	83,0	2.01	51,0	0.55	14,0	0.83	21,0	1 1/8	28,5
K21145-08-12	1/2	12,7	1 3/16 - 14	3.23	82,0	1.97	50,0	0.59	15,0	0.79	20,0	1 3/8	34,9
K21145-10-08	5/8	15,9	13/16 - 16	3.62	92,0	2.09	53,0	0.43	11,0	0.79	20,0	1 1/8	28,5
K21145-10-10	5/8	15,9	1 - 14	3.66	93,1	2.13	54,0	0.55	14,0	0.83	21,0	1 1/8	28,5
K21145-10-12	5/8	15,9	1 3/16 - 12	3.62	92,0	2.09	53,0	0.59	15,0	0.79	20,0	1 3/8	34,9
K21145-12-10	3/4	19,1	1 - 14	4.57	116,1	2.99	76,0	0.55	14,0	1.14	29,0	1 1/8	28,5
K21145-12-12	3/4	19,1	1 3/16 - 12	4.53	115,1	2.96	75,0	0.59	15,0	1.10	28,0	1 3/8	34,9
K21145-12-16	3/4	19,1	1 7/16 - 12	4.53	115,1	2.96	75,0	0.63	16,0	1.18	30,0	1 5/8	41,2
K21145-16-12	1"	25,4	1 3/16 - 12	4.77	121,1	2.99	76,0	0.59	15,0	1.18	30,0	1 3/8	34,9
K21145-16-16	1"	25,4	1 7/16 - 12	4.77	121,1	2.99	76,0	0.63	16,0	1.14	29,0	1 5/8	41,2
K21145-16-20	1"	25,4	1 11/16 - 12	4.89	124,1	3.11	79,0	0.63	16,0	1.30	33,0	1 7/8	47,6
K21145-20-16	1 1/4	31,8	1 7/16 - 12	5.79	147,1	3.94	100,0	0.63	16,0	1.46	37,0	1 7/8	47,6
K21145-20-20	1 1/4	31,8	1 11/16 - 12	5.91	150,1	4.06	103,0	0.63	16,0	1.58	40,0	1 5/8	41,2
K21145-20-24	1 1/4	31,8	2 - 12	5.95	151,1	4.1	104,0	0.63	16,0	1.62	41,0	2 1/4	57,1
K21145-24-24	1 1/2	38,1	2 - 12	6.86	174,1	4.49	114,0	0.63	16,0	1.77	45,0	2 1/4	57,1