

21-2C-NB

General Purpose Rectus 21 Interchange

Notable Features:

- Pneumatic 1/8" Capacity
- Rectus 21 Series Interchange
- Ball-Lock Design
- Provides One-Way Shut-Off
- Nickel Plated Brass Body and Sleeve
- Buna-N Seals
- -0° to +160° F (-17° to +71° C)
- Page Update: 2015-11-01

Rectus 21 Interchange Coupling

Nickel Plated Brass



21-2C-NB

21-2N-NB

Coupler

Part No.	Flow Size	Thread Size	Thread Type	Thread	Working PSI	Reference	
						Alpha	Dixon
21-2C-02F-NB	1/8	1/8	Female	1/8 - 27	300	80112-02	1BRF1-B-7
21-2C-04F-NB	1/8	1/4	Female	1/4 - 18	300	80112-04	1BRF2-B-7
21-2C-06F-NB	1/8	3/8	Female	3/8 - 18	250	80112-06	-
21-2C-5/32H-NB	1/8	5/32	Industrial	Barb	Barb	-	1BRS1.25-B-7
21-2C-04H-NB	1/8	1/4	Industrial	Barb	Barb	-	1BRS1.86-B-7
21-2C-06H-NB	1/8	3/8	Industrial	Barb	Barb	-	1BRS2.83-B-7
21-2C-02M-NB	1/8	1/8	Male	1/8 - 27	250	80111-02	1BRM1-B-7
21-2C-04M-NB	1/8	1/4	Male	1/4 - 18	250	80111-04	1BRM2-B-7
21-2C-06M-NB	1/8	3/8	Male	3/8 - 18	250	80111-06	-

Nipple

Part No.	Flow Size	Thread Size	Thread Type	Thread	Working PSI	Reference	
						Alpha	Dixon
21-2N-02F-NB	1/8	1/8	Female	1/8 - 27	See Coupler	80212-02	BR1F1-B-E-7
21-2N-04F-NB	1/8	1/4	Female	1/4 - 18	See Coupler	80212-04	BR1F2-B-E-7
21-2N-06F-NB	1/8	3/8	Female	3/8 - 18	See Coupler	80212-06	-
21-2N-02M-NB	1/8	1/8	Male	1/8 - 27	See Coupler	80211-02	BR1M1-B-E-7
21-2N-04M-NB	1/8	1/4	Male	1/4 - 18	See Coupler	80211-04	BR1M2-B-E-7
21-2N-06M-NB	1/8	3/8	Male	3/8 - 18	See Coupler	80211-06	-

Crossover references Do Not necessarily match All attributes of the series shown.
Pictures shown as reference only, part look may vary.