


K21100

Female OFS Swivel

Ref. Parker 1JS43



Part No.	1 - Hose Size		2 - Female OFS Sw.	A - Length		B - Cut-Off Allow.		C - Optional Len.		H - Body Hex		W - Nut Hex	
	(in)	(mm)	(in)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
K21100-04-04	1/4	6,4	9/16 - 18	1.89	48,0	1.1	28,0	0.32	8,0	9/16	14,2	11/16	17,4
K21100-04-06	1/4	6,4	11/16 - 16	1.97	50,0	1.18	30,0	0.35	9,0	11/16	17,4	13/16	20,6
K21100-04-08	1/4	6,4	13/16 - 16	2.09	53,0	1.3	33,0	0.43	11,0	11/16	17,4	15/16	23,8
K21100-06-04	3/8	9,5	9/16 - 18	2.21	56,0	1.06	27,0	—	—	11/16	17,4	11/16	17,4
K21100-06-06	3/8	9,5	11/16 - 16	2.21	56,0	1.14	29,0	0.35	9,0	11/16	17,4	13/16	20,6
K21100-06-08	3/8	9,5	13/16 - 16	2.32	59,0	1.26	32,0	0.43	11,0	11/16	17,4	15/16	23,8
K21100-06-10	3/8	9,5	1 - 14	2.6	66,0	1.54	39,0	0.55	14,0	11/16	17,4	1 1/8	28,5
K21100-08-06	1/2	12,7	11/16 - 16	2.36	60,0	1.14	29,0	0.35	9,0	13/16	20,6	13/16	20,6
K21100-08-08	1/2	12,7	13/16 - 16	2.48	63,0	1.26	32,0	0.43	11,0	13/16	20,6	15/16	23,8
K21100-08-10	1/2	12,7	1 - 14	2.76	70,0	1.54	39,0	0.55	14,0	13/16	20,6	1 1/8	28,5
K21100-08-12	1/2	12,7	1 3/16 - 12	2.88	73,0	1.65	42,0	0.59	15,0	15/16	23,8	1 3/8	34,9
K21100-10-08	5/8	15,9	13/16 - 16	2.76	70,0	1.26	32,0	0.43	11,0	15/16	23,8	15/16	23,8
K21100-10-10	5/8	15,9	1 - 14	2.76	70,0	1.54	39,0	0.55	14,0	13/16	20,6	1 1/8	28,5
K21100-10-12	5/8	15,9	1 3/16 - 12	3.15	80,0	1.65	42,0	0.59	15,0	1"	25,4	1 3/8	34,9
K21100-12-10	3/4	19,1	1 - 14	3.07	78,0	1.54	39,0	0.55	14,0	1 1/16	26,9	1 1/8	28,5
K21100-12-12	3/4	19,1	1 3/16 - 12	3.15	80,0	1.62	41,0	0.59	15,0	1 1/8	28,5	1 3/8	34,9
K21100-12-16	3/4	19,1	1 7/16 - 12	3.23	82,0	1.69	43,0	0.63	16,0	1 1/4	31,7	1 5/8	41,2
K21100-16-12	1"	25,4	1 3/16 - 12	3.47	88,0	1.69	43,0	0.59	15,0	1 5/16	33,3	1 3/8	34,9
K21100-16-16	1"	25,4	1 7/16 - 12	3.55	90,0	1.77	45,0	0.63	16,0	1 3/8	34,9	1 5/8	41,2
K21100-16-20	1"	25,4	1 11/16 - 12	3.07	78,0	1.3	33,0	0.63	16,0	1 3/8	34,9	1 7/8	47,6
K21100-20-16	1 1/4	31,8	1 7/16 - 12	3.59	91,0	1.73	44,0	0.63	16,0	1 3/4	44,4	1 5/8	41,2
K21100-20-20	1 1/4	31,8	1 11/16 - 12	3.39	86,0	1.54	39,0	0.63	16,0	1 3/4	44,4	1 7/8	47,6
K21100-20-24	1 1/4	31,8	2 - 12	3.47	88,0	1.62	41,0	0.63	16,0	1 3/4	44,4	2 1/4	57,1
K21100-24-24	1 1/2	38,1	2 - 12	3.94	100,0	1.62	41,0	0.63	16,0	1 7/8	47,6	2 1/4	57,1