


# 2601

## 37° JIC Flare Fittings Male Branch Tee



**Reference**  
Aeroquip 2030  
Parker Hose 213T  
Parker Tube STX  
Weatherhead C5605  
SAE 070425

Part No.	Tube O.D.	1-2 Male JIC	3 Male NPTF	M Length	M1 Length	Y Flats	Operating Pressure
2601-03-03-02-4 #	3/16	3/8 - 24	1/8 - 27	0.83	0.72	7/16	6,000
2601-04-04-02-4	1/4	7/16 - 20	1/8 - 27	0.89	0.78	7/16	6,000
2601-04-04-04-4	1/4	7/16 - 20	1/4 - 18	1.05	1.09	9/16	6,000
2601-04-04-06-4 #	1/4	7/16 - 20	3/8 - 18	1.12	1.22	3/4	6,000
2601-05-05-02-4 #	5/16	1/2 - 20	1/8 - 27	0.95	0.78	9/16	6,000
2601-05-05-04-4 #	5/16	1/2 - 20	1/4 - 18	1.05	1.09	9/16	6,000
2601-06-06-04-4	3/8	9/16 - 18	1/4 - 18	1.06	1.09	9/16	6,000
2601-06-06-06-4	3/8	9/16 - 18	3/8 - 18	1.14	1.22	3/4	6,000
2601-06-06-08-4	3/8	9/16 - 18	1/2 - 14	1.22	1.47	7/8	6,000
2601-08-08-06-4	1/2	3/4 - 16	3/8 - 18	1.25	1.22	3/4	6,000
2601-08-08-08-4	1/2	3/4 - 16	1/2 - 14	1.33	1.47	7/8	6,000
2601-10-10-08-4	5/8	7/8 - 14	1/2 - 14	1.45	1.47	7/8	5,000
2601-12-12-08-4 #	3/4	1 1/16 - 12	1/2 - 14	1.66	1.59	1 1/16	5,000
2601-12-12-12-4	3/4	1 1/16 - 12	3/4 - 14	1.66	1.59	1 1/16	4,000
2601-14-14-12-4 #	7/8	1 3/16 - 12	3/4 - 14	1.81	1.72	1 5/16	4,000
2601-16-16-16-4	1"	1 5/16 - 12	1 - 11 1/2	1.81	1.97	1 5/16	3,000
2601-20-20-20-4	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	2.06	2.38	1 5/8	2,500
2601-32-32-32-4 #	2"	2 1/2 - 12	2 - 11 1/2	3.06	3.00	2 1/2	2,000

● Available in 316 Stainless Steel

4:1 Safety Factor

# Minimum Order Quantity May Apply.