


GagePort Series

GagePort Series information is on page 12

GP-6400

Male JIC x Male Boss
ORB & Pipe Ports

SAE J514



GP-6400-①-②-③P ①-MJ ②-MB ③-Pipe Port	Tube O.D.	① Male JIC	② Male ORB	③ NPTF Port	C Nut Hex	L Length	Operating Pressure
GP-6400-06-06-2P	3/8	9/16 - 18	9/16 - 18	1/8 - 27	3/4	2.48	6,000
GP-6400-06-06-4P ①	3/8	9/16 - 18	9/16 - 18	1/4 - 18	3/4	2.48	6,000
GP-6400-06-06-6P	3/8	9/16 - 18	9/16 - 18	3/8 - 18	3/4	2.48	6,000
GP-6400-08-08-2P	1/2	3/4 - 16	3/4 - 16	1/8 - 27	15/16	2.74	6,000
GP-6400-08-08-4P	1/2	3/4 - 16	3/4 - 16	1/4 - 18	15/16	2.74	6,000
GP-6400-08-08-6P	1/2	3/4 - 16	3/4 - 16	3/8 - 18	15/16	2.74	6,000
GP-6400-10-10-2P	5/8	7/8 - 14	7/8 - 14	1/8 - 27	1"	3.12	5,000
GP-6400-10-10-4P	5/8	7/8 - 14	7/8 - 14	1/4 - 18	1"	3.12	5,000
GP-6400-10-10-6P	5/8	7/8 - 14	7/8 - 14	3/8 - 18	1"	3.12	5,000
GP-6400-12-12-2P	3/4	1 1/16 - 12	1 1/16 - 12	1/8 - 27	1 3/8	3.76	5,000
GP-6400-12-12-4P	3/4	1 1/16 - 12	1 1/16 - 12	1/4 - 18	1 3/8	3.76	5,000
GP-6400-12-12-6P	3/4	1 1/16 - 12	1 1/16 - 12	3/8 - 18	1 3/8	3.76	5,000
GP-6400-12-12-8P ②	3/4	1 1/16 - 12	1 1/16 - 12	1/2 - 14	1 3/8	3.76	5,000

① Ref. Caterpillar 6V-3297. ② Ref. Caterpillar 6V-9039.

4:1 Safety Factor

Please Note

For a full 360° horizontal adjustment, insert series GP-6405 (p.15) into an O-ring port.